

### GRM 302 30 L

**Single phase 110V, 240V or 3 phase 415V**

Supplied fitted with appropriate plug and full user instructions.

**Height** 860 mm x **Width** - overall 500 mm x **Depth** 560 mm

**Weight** 50 kg.

#### SPECIFICATION (CE standard)

- Electric control box
- Indicators
  - Delivery line - visual indicator with combined electric cut-out switch
  - Nitrile seals
  - Flexible hoses – 2 metres long, suction & outlet
  - Heavy duty trolley & wheels
  - **Inlet (pump protection) filtration** – micron metal mesh
  - **Delivery filtration “Spin-on” type** – See Options below
  - Inline contamination monitor (ICM) fitted



**A complete range  
of off line  
filling/filtration  
units**



### Spare Parts

#### Filter element - Standard length

Inorganic microfibre element

CS 100 A01 A P01	1 µm absolute
CS 100 A03 A P01	3 µm absolute
CS 100 A06 A P01	6 µm absolute
CS 100 A10 A P01	10 µm absolute
CS 100 A25 A P01	25 µm absolute
Wire mesh element	
CS 100 M25 A P01	25 µm
CS 100 M60 A P01	60 µm

CS 100 M60 A P01 60 µm

#### Filter element - Extended length

Inorganic microfibre element

CS 150 A01 A P01	1 µm absolute
CS 150 A03 A P01	3 µm absolute
CS 150 A06 A P01	6 µm absolute
CS 150 A10 A P01	10 µm absolute
CS 150 A25 A P01	25 µm absolute
Wire mesh element	
CS 150 M25 A P01	25 µm
CS 150 M60 A P01	60 µm

**and more..**

### GRM302 OUTLET FILTRATION OPTIONS

Outlet filtration micron options available:

#### CS150 A SERIES

3, 6, 10 and 25 micron absolute. Effective area - 5390 cm<sup>2</sup>

#### CS150 P SERIES

10 and 25 micron nominal. Effective area - 5760 cm<sup>2</sup>

#### GRM302 - Water removal options available:

#### CW150 P SERIES

10 & 25 micron nominal removing 0.79 litres of water while filtering oil at 10 or 25 micron nominal filtration

**Please note: filtration is not included and should be ordered separately**

### Ordering information

**GRM302**

**Example: GRM**

<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>
----------	----------	----------	----------	----------

**1 - Flow**

**30** 30L/min      **2** 0.75kW

**5 - Filtration**

**S** No filter fitted, to be ordered separately - see spare parts

**2 - Electrical power**

**1** 110V single phase

**2** 240V single phase

**3** 415V 4 phase

**3 - Electric motor**

**4 - Replacement suction element**

**M149** 173µm cleanable element



**...because contamination costs!**

