


drain connection ( $P_{\text{drain}} < 0,5 \text{ bar}$ )  
(Always connect directly to the tank)

Symbol



Type for 4xØ11:  
30MR...X568HG(M)F

Type	Displacement cm <sup>3</sup>	Pressure Pmax, [bar]	Speed n [min <sup>-1</sup> ]	Dimensions					
				A	B	Inlet		Outlet	
						M	G	M	G
				mm		mm	"	mm	"
30MR22.5X568HG(M)	22.5	200	500 ... 2500	57.6	119.7	M27x1.5	G3/4-A	M27x1.5	G3/4-A
30MR25X568HG(M)	25	200	500 ... 2500	58.3	121.1	M27x1.5	G3/4-A	M27x1.5	G3/4-A
30MR28X568HG(M)	28	200	500 ... 2500	60.2	124.7	M27x1.5	G3/4-A	M27x1.5	G3/4-A
30MR32X568HG(M)	32	200	500 ... 2500	66.5	137.3	M33x1.5	G1-A	M33x1.5	G1-A
30MR36X568HG(M)	36	200	500 ... 2300	68	140.5	M33x1.5	G1-A	M33x1.5	G1-A
30MR42X568HG(M)	42	200	500 ... 2300	70.8	146.1	M33x1.5	G1-A	M33x1.5	G1-A
30MR46X568HG(M)	46	200	500 ... 2100	72.7	149.8	M33x1.5	G1-A	M33x1.5	G1-A
30MR50X568HG(M)	50	200	500 ... 2100	74.5	153.4	M33x1.5	G1-A	M33x1.5	G1-A
30MR55X568HG(M)	55	200	500 ... 1750	76.7	157.9	M33x1.5	G1-A	M33x1.5	G1-A
30MR60X568HG(M)	60	180	500 ... 1750	78.7	162.4	M33x1.5	G1-A	M33x1.5	G1-A