


Quick reference guide

Filter series	VISUAL INDICATOR	ELECTRICAL INDICATOR	ELECTRICAL/VISUAL INDICATOR	ELECTRONIC INDICATOR
Suction filters				
SF2 250 - 251 - 350 SF2 500 - 501 - 502 - 503 - 504 - 505 SF2 510 - 535 - 540 FAS	VVA16P01 VVR16P01	VEA21AA50P01	VLA21AA51P01 VLA21AA52P01 VLA21AA53P01 VLA21AA71P01	
Return filters				
MPF - MPT with bypass 1,75 bar MPH with bypass 1,75 bar	BVA14P01 BVR14P01 BVP15HAP01 BVP15HMP01	BEA15HA50P01 BEM15HA41P01	BLA15HA51P01 BLA15HA52P01 BLA15HA53P01 BLA15HA71P01	
MPF - MPT with bypass 3 bar MPH with bypass 2,5 bar FRI 255 RF2 250	BVA25P01 BVR25P01 BVP20HAP01 BVP20HMP01	BEA20HA50P01 BEM20HA41P01	BLA20HA51P01 BLA20HA52P01 BLA20HA53P01 BLA20HA71P01	
FRI 025 - 040 - 100 - 250 - 630 - 850	DVA20xP01 DVM20xP01	DEA20xA50P01 DEM20xAxxP01	DLA20xA51P01 DLA20xA52P01 DLA20xA71P01 DLE20xA50P01 DLE20xF50P01	DTA20xF70P01
Return/Suction filters				
MRSX 116 - 165 - 166 Suction line	VVB16P01 VVS16P01	VEB21AA50P01	VLB21AA51P01 VLB21AA52P01 VLB21AA53P01 VLB21AA71P01	
MRSX 116 - 165 - 166 Return line	BVA25P01 BVR25P01 BVP20HAP01 BVP205HMP01	BEA25HA50P01 BEM25HA41P01 BET25HF10P01 BET25HF30P01 BET25HF50P01	BLA25HA51P01 BLA25HA52P01 BLA25HA53P01 BLA25HA71P01	
Spin-On filters				
MPS 050 - 070 - 100 - 150 MPS 200 - 250 - 300 - 350 Suction line	VVB16P01 VVS16P01	VEB21AA50P01	VLB21AA51P01 VLB21AA52P01 VLB21AA53P01 VLB21AA71P01	
MPS 050 - 070 - 100 - 150 MPS 200 - 250 - 300 - 350 MST 050 - 070 - 100 - 150 Return line	BVA14P01 BVR14P01 BVP15HAP01 BVP15HMP01	BEA15HA50P01 BEM15HA41P01	BLA15HA51P01 BLA15HA52P01 BLA15HA53P01 BLA15HA71P01	
MPS 051 - 071 - 101 - 151 MPS 301 - 351 MSH 050 - 070 - 100 - 150 In-line	DVA12xP01 DVM12xP01	DEA12xA50P01 DEM12xAxxP01	DLA12xA51P01 DLA12xA52P01 DLA12xA71P01 DLE12xA50P01 DLE12xF50P01	

Filter series	VISUAL INDICATOR	ELECTRICAL INDICATOR	ELECTRICAL/VISUAL INDICATOR	ELECTRONIC INDICATOR
Low Pressure In-Line filters				
LMP 110 - 112 - 116 - 118 - 119 LMP 120 - 122 - 123 LMP 210 - 211 LMP 400 - 401 - 430 - 431 LMP 900 - 901 - 950 - 951 LMD 400 - 401 - 431 - 951 With bypass valve	DVA20xP01 DVM20xP01	DEA20xA50P01 DEM20xAxxP01	DLA20xA51P01 DLA20xA52P01 DLA20xA71P01 DLE20xA50P01 DLE20xF50P01	DTA20xF70P01
LMP 110 - 112 - 116 - 118 - 119 LMP 120 - 122 - 123 LMP 210 - 211 LMP 400 - 401 - 430 - 431 LMP 900 - 901 - 950 - 951 LMD 400 - 401 - 431 - 951 MPD 250 - 251 Without bypass valve	DVA50xP01 DVM50xP01	DEA50xA50P01 DEM50xAxxP01	DLA50xA51P01 DLA50xA52P01 DLA50xA71P01 DLE50xA50P01 DLE50xF50P01	DTA50xF70P01
High Pressure In-Line filters				
FMP 039 - 065 - 135 - 320 FMM 050 FHP 010 - 011 - 065 - 135 - 320 - 500 FHB 050 - 135 - 320 FHM 006 - 007 - 010 - 050 - 135 - 320 - 500 FHF 325 FHD 021 - 051 - 326 - 333 With bypass valve	DVA50xP01 DVM50xP01	DEA50xA50P01 DEM50xAxxP01	DLA50xA51P01 DLA50xA52P01 DLA50xA71P01 DLE50xA50P01 DLE50xF50P01	DTA50xF70P01
FMP 039 - 065 - 135 - 320 FMM 050 FHP 010 - 011 - 065 - 135 - 320 - 500 FHB 050 - 135 - 320 FHM 006 - 007 - 010 - 050 - 135 - 320 - 500 FHF 325 FHD 021 - 051 - 326 - 333 Without bypass valve	DVA70xP01 DVM70xP01	DEA70xA50P01 DEM70xAxxP01	DLA70xA51P01 DLA70xA52P01 DLA70xA71P01 DLE70xA50P01 DLE70xF50P01	DTA70xF70P01
Stainless Steel High Pressure In-Line filters				
FZB 039 FZM 039 FZP 039 - 136 FZH 010 - 011 - 039 FZD 051 With bypass valve	DVX50xP01 DVY50xP01	DEX50xA50P01	DLX50xA51P01 DLX50xA52P01	
FZB 039 FZM 039 FZP 039 - 136 FZH 010 - 011 - 039 FZD 010 - 021 - 051 Without bypass valve	DVX70xP01 DVY70xP01	DEX70xA50P01	DLX70xA51P01 DLX70xA52P01	

VACUUM INDICATORS

VEA - VEB



Available connections:
R 1/4" EN 10226 (VEA21AA50P01)
R 1/8" EN 10226 (VEB21AA50P01)

Electrical Vacuum Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: NBR


Technical data:

- Indicator type: Electrical vacuum indicator
- Setting pressure: -0,21 bar $\pm 10\%$
- Max working pressure: 10 bar
- Proof pressure: 15 bar
- Working temperature: From -25 °C to +80 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 5 A / 14 Vdc
4 A / 30 Vdc
5 A / 125 Vac
5 A / 250 Vac
- Electrical connections: 50 - EN 175301-803
- Protection degree: IP 65 in according to EN 60529
- Available ATEX product: II 1GD Ex ia IIC Tx Ex ia IIIC Tx °C X


HYDRAULIC SYMBOL



ELECTRICAL SYMBOL



VLA - VLB



Available connections:
R 1/4" EN 10226 (VLA21AAxxP01)
R 1/8" EN 10226 (VLB21AAxxP01)

Electrical/Visual Vacuum Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: NBR


Technical data:

- Indicator type: Electrical/Visual vacuum indicator
- Setting pressure: -0,21 bar $\pm 10\%$
- Max working pressure: 10 bar
- Proof pressure: 15 bar
- Working temperature: From -25 °C to +80 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 51: 0,8 A / 24 Vdc
52: 0,2 A / 115 Vdc
53: 4 A / 230 Vdc
- Electrical connections: 51 - EN 175301-803 (24 Vdc lamps)
52 - EN 175301-803 (110 Vdc lamps)
53 - EN 175301-803 (230 Vac lamps)
- Protection degree: IP 65 in according to EN 60529


HYDRAULIC SYMBOL



ELECTRICAL SYMBOL



VLA - VLB



Available connections:
R 1/4" EN 10226 (VLA21AA71P01)
R 1/8" EN 10226 (VLB21AA71P01)

Electrical/Visual Vacuum Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: NBR


Technical data:

- Indicator type: Electrical/Visual vacuum indicator
- Setting pressure: -0,21 bar $\pm 10\%$
- Max working pressure: 10 bar
- Proof pressure: 15 bar
- Working temperature: From -25 °C to +80 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 0,4 A / 24 Vdc
- Electrical connections: 71 - M12 IEC 61076-2-101 (24 Vdc lamps)
- Protection degree: IP 65 in according to EN 60529

HYDRAULIC SYMBOL




ELECTRICAL SYMBOL




VACUUM INDICATORS

VVA - VVB



R 1/4" - EN 10226
R 1/8" - EN 10226



Available connections:
R 1/4" EN 10226 (VVA16P01)
R 1/8" EN 10226 (VVB16P01)

Axial Vacuum Gauge

Materials:

- Case: Painted Steel
- Window: Clear plastic
- Dial: Painted Steel
- Pointer: Painted Aluminium
- Pressure connection: Brass
- Pressure element: Bourdon tub Cu-alloy soft soldered

Technical data:

- Indicator type: Axial vacuum gauge
- Max working pressure: Static: 7 bar
Fluctuating: 6 bar
Short time: 10 bar
- Working temperature: From -40 °C to +60 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943
- Accuracy class: cl. 2.5
- Protection degree: IP 31 in according to EN 60529

HYDRAULIC SYMBOL




GRADUATED DISPLAY

GREEN BACKGROUND
(from 0 to -12 cmHg)
Clean filter element


YELLOW BACKGROUND
(from -12 to -18 cmHg)
Warning

RED BACKGROUND
(from -18 to -76 cmHg)
Bypass

VVR - VVS



R 1/4" - EN 10226
R 1/8" - EN 10226



Available connections:
R 1/4" EN 10226 (VVR16P01)
R 1/8" EN 10226 (VVS16P01)

Radial Vacuum Gauge

Materials:

- Case: Painted Steel
- Window: Clear plastic
- Dial: Painted Steel
- Pointer: Painted Aluminium
- Pressure connection: Brass
- Pressure element: Bourdon tub Cu-alloy soft soldered

Technical data:

- Indicator type: Radial vacuum gauge
- Max working pressure: Static: 7 bar
Fluctuating: 6 bar
Short time: 10 bar
- Working temperature: From -40 °C to +60 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943
- Accuracy class: cl. 2.5
- Protection degree: IP 31 in according to EN 60529

HYDRAULIC SYMBOL



GRADUATED DISPLAY

GREEN BACKGROUND
(from 0 to -12 cmHg)
Clean filter element

YELLOW BACKGROUND
(from -12 to -18 cmHg)
Warning

REDBACKGROUND
(from -18 to -76 cmHg)
Bypass

Ordering information VE - VL - VV

Series	1	2	3	4	5	6	7
VE							
Example:	VE	A	21	A	A	50	P01

Series	1	2	3	4	5	6	7
VL							
Example:	VL	A	21	A	A	52	P01

Series	1	2	3	7
VV				
Example:	VV	A	16	P01

1 - Series

VE	Electrical indicator
VL	Electrical/Visual indicator
VV	Visual indicator

2 - Type

VE - VL series

A	R 1/4" EN 10226 connection
B	R 1/8" EN 10226 connection

VV series

A	Axial vacuumeter R 1/4" EN 10226 connection
B	Axial vacuumeter R 1/8" EN 10226 connection
R	Radial vacuumeter R 1/4" EN 10226 connection
S	Radial vacuumeter R 1/8" EN 10226 connection

3 - Setting pressure

VEA - VLA series

21	-0,21 bar
-----------	-----------

VVA - VVR series

16	-0,16 bar
-----------	-----------

4 - Seals (excluded for VV)

A	NBR
	On request

5 - Thermostat (excluded for VV)

A	Without thermostat
----------	--------------------

6 - Electrical connection (excluded for VV)

VEA series

50	EN 175301-803 connector
-----------	-------------------------

VLA series


51	EN 175301-803 clear connector with 24 V lamps
52	EN 175301-803 clear connector with 110 V lamps
53	EN 175301-803 clear connector with 230 V lamps
71	M12 IEC 61076-2-101 clear connector with 24 V lamps

7 - Option

P01	MP Filtri standard
Pxx	Customer request

BAROMETRIC INDICATORS

BEA



Available setting:
1,5 bar $\pm 10\%$ (BEA15HA50P01)
2 bar $\pm 10\%$ (BEA20HA50P01)

Electrical Pressure Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: NBR


Technical data:

- Indicator type: Electrical pressure indicator
- Max working pressure: 40 bar
- Proof pressure: 60 bar
- Working temperature: From -25 °C to +80 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 5 A / 14 VDC
4 A / 30 VDC
5 A / 125 VAC
5 A / 250 VAC
- Electrical connections: 50 - EN 175301-803
- Protection degree: IP 65 in according to EN 60529
- Available Atex product: II 1GD Ex ia IIC Tx Ex ia IIC Tx °C X


HYDRAULIC SYMBOL



ELECTRICAL SYMBOL



BEM



Available setting:
1,5 bar $\pm 10\%$ (BEM15HA50P01)
2 bar $\pm 10\%$ (BEM20HA50P01)

Electrical Pressure Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: HNBR

Technical data:


- Indicator type: Electrical pressure indicator
- Max working pressure: 40 bar
- Proof pressure: 60 bar
- Working temperature: From -25 °C to +80 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943

Electrical data:


- Resistive load: 5 A / 14 VDC
4 A / 30 VDC
5 A / 125 VAC
5 A / 250 VAC
- Electrical connections: 50 - EN 175301-803
- Protection degree: IP 67 in according to EN 60529

On request this indicator can be provided with main connectors in use for wirings.


HYDRAULIC SYMBOL



ELECTRICAL SYMBOL



BLA



Available setting:
1,5 bar $\pm 10\%$ (BLA15HAxxP01)
2 bar $\pm 10\%$ (BLA20HAxxP01)

Electrical/Visual Pressure Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: NBR


Technical data:

- Indicator type: Electrical/Visual pressure indicator
- Max working pressure: 40 bar
- Proof pressure: 60 bar
- Working temperature: From -25 °C to +80 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 51: 0,8 A / 24 VDC
52: 0,2 A / 115 VDC
53: 4 A / 230 VDC
- Electrical connections: 51 - EN 175301-803 (24 VDC lamps)
52 - EN 175301-803 (110 VDC lamps)
53 - EN 175301-803 (230 VAC lamps)
- Protection degree: IP 65 in according to EN 60529

HYDRAULIC SYMBOL




ELECTRICAL SYMBOL



BAROMETRIC INDICATORS

BET



Available setting:
2,5 bar $\pm 10\%$ (BET25HF10P01)

Electrical Pressure Indicator

Materials:

- Body: Brass
- Base - Ring: Nylon
- Contact: Silver
- Seals: HNBR


Technical data:

- Pressure switch type: Electrical pressure switch
- Pressure setting: 2,5 bar $\pm 10\%$
- Working pressure: 10 bar
- Proof pressure: 15 bar
- Max working temperature: $+100^\circ\text{C}$
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Electrical condition: Normally opened single contact
- Resistive load: 0,5 A / 48 VDC
- Electrical connections: 10 - AMP Superseal series 1,5
- Thermostat condition: Open up to 30°C
- CE certification
- Protection degree: IP 65 in according to EN 60529


HYDRAULIC SYMBOL



ELECTRICAL SYMBOL



BET



Available setting:
2,5 bar $\pm 10\%$ (BET25HF30P01)

Electrical Pressure Indicator

Materials:

- Body: Brass
- Base - Ring: Nylon
- Contact: Silver
- Seals: HNBR


Technical data:

- Pressure switch type: Electrical pressure switch
- Pressure setting: 2,5 bar $\pm 10\%$
- Working pressure: 10 bar
- Proof pressure: 15 bar
- Max working temperature: $+100^\circ\text{C}$
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Electrical condition: Normally opened single contact
- Resistive load: 0,5 A / 48 Vdc
- Electrical connections: 35 - Deutsch DT-04-3-P
- Thermostat condition: Open up to 30°C
- CE certification
- Protection degree: IP 65 in according to EN 60529


HYDRAULIC SYMBOL



ELECTRICAL SYMBOL



BET



Available setting:
2,5 bar $\pm 10\%$ (BET25HF50P01)

Electrical Pressure Indicator

Materials:

- Body: Brass
- Base - Ring: Nylon
- Contact: Silver
- Seals: HNBR


Technical data:

- Pressure switch type: Electrical pressure switch
- Pressure setting: 2,5 bar $\pm 10\%$
- Working pressure: 10 bar
- Proof pressure: 15 bar
- Max working temperature: $+100^\circ\text{C}$
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Electrical condition: Normally opened single contact
- Resistive load: 0,5 A / 48 Vdc
- Electrical connections: 50 - EN 175301-803
- Thermostat condition: Open up to 30°C
- CE certification
- Protection degree: IP 65 in according to EN 60529

HYDRAULIC SYMBOL




ELECTRICAL SYMBOL



BAROMETRIC INDICATORS

BLA



Available setting:
1,5 bar $\pm 10\%$ (BLA15HA71P01)
2 bar $\pm 10\%$ (BLA20HA71P01)

Electrical/Visual Pressure Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: NBR


Technical data:

- Indicator type: Electrical/Visual pressure indicator
- Max working pressure: 40 bar
- Proof pressure: 60 bar
- Working temperature: From -25 °C to +80 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 0,4 A / 24 VDC
- Electrical connections: 71 - M12 IEC 61076-2-101 (24 Vdc lamps)
- Protection degree: IP 65 in according to EN 60529


HYDRAULIC SYMBOL




ELECTRICAL SYMBOL



BVA



R 1/8" - EN 10226



Available setting:
1,4 bar $\pm 10\%$ (BVA14P01)
2,5 bar $\pm 10\%$ (BVA25P01)

Axial Pressure Gauge

Materials:

- Case: Painted Steel
- Window: Clear plastic
- Dial: Painted Steel
- Pointer: Painted Aluminium
- Pressure connection: Brass
- Pressure element: Bourdon tub cu-alloy soft soldered

Technical data:

- Indicator type: Axial pressure gauge
- Max working pressure: Static: 7 bar
Fluctuating: 6 bar
Short time: 10 bar
- Working temperature: From -40 °C to +60 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943
- Accuracy class: cl. 2.5
- Protection degree: IP 31 in according to EN 60529


HYDRAULIC SYMBOL




GRADUATED DISPLAY

BVA14P01
GREEN BACKGROUND (from 0 to 1,4 bar)
Clean filter element
YELLOW BACKGROUND (from 1,4 to 1,7 bar)
Warning
RED BACKGROUND (from 1,7 to 10 bar)
Bypass
BVA25P01
GREEN BACKGROUND (from 0 to 2,5 bar)
Clean filter element
YELLOW BACKGROUND (from 2,5 to 3 bar)
Warning
RED BACKGROUND (from 3 to 10 bar)
Bypass

BVR



R 1/8" - EN 10226



Available setting:
1,4 bar $\pm 10\%$ (BVR14P01)
2,5 bar $\pm 10\%$ (BVR25P01)

Radial Pressure Gauge

Materials:

- Case: Painted Steel
- Window: Clear plastic
- Dial: Painted Steel
- Pointer: Painted Aluminium
- Pressure connection: Brass
- Pressure element: Bourdon tub cu-alloy soft soldered

Technical data:

- Indicator type: Radial pressure gauge
- Max working pressure: Static: 7 bar
Fluctuating: 6 bar
Short time: 10 bar
- Working temperature: From -40 °C to +60 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943
- Accuracy class: cl. 2.5
- Protection degree: IP 31 in according to EN 60529

HYDRAULIC SYMBOL




GRADUATED DISPLAY

BVR14P01
GREEN BACKGROUND (from 0 to 1,4 bar)
Clean filter element
YELLOW BACKGROUND (from 1,4 to 1,7 bar)
Warning
RED BACKGROUND (from 1,7 to 10 bar)
Bypass
BVR25P01
GREEN BACKGROUND (from 0 to 2,5 bar)
Clean filter element
YELLOW BACKGROUND (from 2,5 to 3 bar)
Warning
RED BACKGROUND (from 3 to 10 bar)
Bypass

BAROMETRIC INDICATORS

BVP - BVQ



Available setting:
1,5 bar $\pm 10\%$ (BVP15AP01 - BVQ15AP01)
2 bar $\pm 10\%$ (BVP20AP01 - BVQ20AP01)

Visual Pressure Indicator

Materials:

- Body: Brass
- Internal parts: Nylon
- Seals: NBR

Technical data:


- Indicator type: Visual pressure indicator
- Reset: BVP - Automatic reset
BVQ - Manual reset
- Max working pressure: 10 bar
- Proof pressure: 15 bar
- Working temperature: From -25°C to $+80^{\circ}\text{C}$
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943
- Protection degree: IP 45 in according to EN 60529

HYDRAULIC SYMBOL




SIGNALS

GREEN BUTTON: INLET PRESSURE



RED BUTTON: CLOGGED FILTER ELEMENT



Ordering information BE - BL - BV

Series

BE

Example:

1	2	3	4	5	6	7

BE A 20 H A 50 P01

Series

BL

Example:

1	2	3	4	5	6	7

BL A 20 H A 52 P01

Series

BV

Example:

1	2	3	4	7

BV P 20 H P01

Series

BV

Example:

1	2	3	7

BV A 14 P01

1 - Series

- ☐ **BE** Electrical indicator
- ☐ **BL** Electrical/Visual indicator
- ☐ **BV** Visual indicator

2 - Type

BE series

- ☐ **A** Standard type
- ☐ **M** With wired connector

BL series

- ☐ **A** Standard type

BV series

- ☐ **A** Axial manometer
- ☐ **R** Radial manometer
- ☐ **P** Visual pressure indicator - Automatic reset
- ☐ **Q** Visual pressure indicator - Manual reset

3 - Setting pressure

BEA - BEM - BLA - BVP series

- ☐ **15** 1,5 bar
- ☐ **20** 2 bar

BVA - BVR series

- ☐ **14** 1,4 bar
- ☐ **25** 2,5 bar

4 - Seals (excluded for BVA - BVR)

- ☐ **H** HNBR
- ☐ On request

5 - Thermostat (excluded for BV)

- ☐ **A** Without thermostat

6 - Electrical connection (excluded for BV)

BEA series

- ☐ **50** EN 175301-803 connector

BEM series

- ☐ **41** Four core cable
- ☐ On request

BLA series


- ☐ **51** EN 175301-803 clear connector with 24 V lamps
- ☐ **52** EN 175301-803 clear connector with 110 V lamps
- ☐ **53** EN 175301-803 clear connector with 230 V lamps
- ☐ **71** M12 IEC 61076-2-101 clear connector with 24 V lamps

7 - Option

- ☐ **P01** MP Filtri standard
- ☐ **Pxx** Customer request

DIFFERENTIAL INDICATORS

DEA



Available setting:

- 1,2 bar $\pm 10\%$ (DEA12xA50P01)
- 2 bar $\pm 10\%$ (DEA20xA50P01)
- 5 bar $\pm 10\%$ (DEA50xA50P01)
- 7 bar $\pm 10\%$ (DEA70xA50P01)
- 9,5 bar $\pm 10\%$ (DEA95xA50P01)

Electrical Differential Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: HNBR - FPM


Technical data:

- Indicator type: Electrical differential indicator
- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25 °C to +110 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 0,2 A / 115 Vdc
- Electrical connections: 50 - EN 175301-803
- Protection degree: IP 66 in according to EN 60529
IP 69K in according to ISO 20653


HYDRAULIC SYMBOL



ELECTRICAL SYMBOL



DEM



Available setting:

- 1,2 bar $\pm 10\%$ (DEM12xx10P01)
- 2 bar $\pm 10\%$ (DEM20xx10P01)
- 5 bar $\pm 10\%$ (DEM50xx10P01)
- 7 bar $\pm 10\%$ (DEM70xx10P01)
- 9,5 bar $\pm 10\%$ (DEM95xx10P01)

Electrical Differential Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: HNBR - FPM


Technical data:

- Indicator type: Electrical differential indicator
- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25 °C to +110 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 0,2 A / 115 Vdc
- Electrical connections: 10 - AMP Superseal series 1,5
- Switching type: Normally open contacts (N.C. on request)
- Thermal lockout: Normally open up to 30 °C (F option)
- Protection degree: IP 66 in according to EN 60529


HYDRAULIC SYMBOL



ELECTRICAL SYMBOL



DEM



Available setting:

- 1,2 bar $\pm 10\%$ (DEM12xx20P01)
- 2 bar $\pm 10\%$ (DEM20xx20P01)
- 5 bar $\pm 10\%$ (DEM50xx20P01)
- 7 bar $\pm 10\%$ (DEM70xx20P01)
- 9,5 bar $\pm 10\%$ (DEM95xx20P01)

Electrical Differential Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: HNBR - FPM


Technical data:

- Indicator type: Electrical differential indicator
- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25 °C to +110 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 0,2 A / 115 Vdc
- Electrical connections: 20 - AMP Time junior
- Switching type: Normally open contacts (N.C. on request)
- Thermal lockout: Normally open up to 30 °C (F option)
- Protection degree: IP 66 in according to EN 60529

HYDRAULIC SYMBOL




ELECTRICAL SYMBOL



DIFFERENTIAL INDICATORS

DEM



Available setting:
 1,2 bar $\pm 10\%$ (DEM12xx30P01)
 2 bar $\pm 10\%$ (DEM20xx30P01)
 5 bar $\pm 10\%$ (DEM50xx30P01)
 7 bar $\pm 10\%$ (DEM70xx30P01)
 9,5 bar $\pm 10\%$ (DEM95xx30P01)

Electrical Differential Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: HNBR - FPM


Technical data:

- Indicator type: Electrical differential indicator
- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25°C to $+110^{\circ}\text{C}$
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 0,2 A / 115 Vdc
- Electrical connections: 30 - Deutsch DT-04-2-P
- Switching type: Normally open contacts (N.C. on request)
- Thermal lockout: Normally open up to 30°C (F option)
- Protection degree: IP 66 in according to EN 60529


HYDRAULIC SYMBOL



ELECTRICAL SYMBOL



DEM



Available setting:
 1,2 bar $\pm 10\%$ (DEM12xx35P01)
 2 bar $\pm 10\%$ (DEM20xx35P01)
 5 bar $\pm 10\%$ (DEM50xx35P01)
 7 bar $\pm 10\%$ (DEM70xx35P01)
 9,5 bar $\pm 10\%$ (DEM95xx35P01)

Electrical Differential Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: HNBR - FPM


Technical data:

- Indicator type: Electrical differential indicator
- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25°C to $+110^{\circ}\text{C}$
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 0,2 A / 115 Vdc
- Electrical connections: 35 - Deutsch DT-04-3-P
- Switching type: SPDT contact
- Thermal lockout: Normally open up to 30°C (F option)
- Protection degree: IP 66 in according to EN 60529


HYDRAULIC SYMBOL



ELECTRICAL SYMBOL



DLA



Available setting:
 1,2 bar $\pm 10\%$ (DLA12xAxxP01)
 2 bar $\pm 10\%$ (DLA20xAxxP01)
 5 bar $\pm 10\%$ (DLA50xAxxP01)
 7 bar $\pm 10\%$ (DLA70xAxxP01)
 9,5 bar $\pm 10\%$ (DLA95xAxxP01)

Electrical/Visual Differential Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: HNBR - FPM


Technical data:

- Indicator type: Electrical/Visual differential indicator
- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25°C to $+110^{\circ}\text{C}$
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 51: 0,8 A / 24 Vdc
52: 0,2 A / 115 Vdc
- Electrical connections: 51 - EN 175301-803 (24 Vdc lamps)
52 - EN 175301-803 (110 Vdc lamps)
- Protection degree: IP 66 in according to EN 60529
IP 69K in according to ISO 20653

HYDRAULIC SYMBOL




ELECTRICAL SYMBOL



DIFFERENTIAL INDICATORS

DLA



Available setting:

- 1,2 bar $\pm 10\%$ (DLA12xA71P01)
- 2 bar $\pm 10\%$ (DLA20xA71P01)
- 5 bar $\pm 10\%$ (DLA50xA71P01)
- 7 bar $\pm 10\%$ (DLA70xA71P01)
- 9,5 bar $\pm 10\%$ (DLA95xA71P01)

Electrical/Visual Differential Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: HNBR - FPM


Technical data:

- Indicator type: Electrical/Visual differential indicator
- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25 °C to +110 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 0,4 A / 24 Vdc
- Electrical connections: 71 - M12 IEC 61076-2-101 (24 Vdc lamps)
- Protection degree: IP 65 in according to EN 60529
IP 69K in according to ISO 20653


HYDRAULIC SYMBOL



ELECTRICAL SYMBOL



DLE



Available setting:

- 1,2 bar $\pm 10\%$ (DLE12VA50P01)
- 2 bar $\pm 10\%$ (DLE20VA50P01)
- 5 bar $\pm 10\%$ (DLE50VA50P01)
- 7 bar $\pm 10\%$ (DLE70VA50P01)
- 9,5 bar $\pm 10\%$ (DLE95VA50P01)

Electrical/Visual Differential Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: FPM

Technical data:


- Indicator type: Electrical/Visual differential indicator
- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25 °C to +110 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943

Electrical data:


- Resistive load: 5 A / 250 VAC
- Electrical connections: 50 - EN 175301-803
- Protection degree: IP 65 in according to EN 60529

Available the connector with lamps


HYDRAULIC SYMBOL



ELECTRICAL SYMBOL



DLE



Available setting:

- 1,2 bar $\pm 10\%$ (DLE12VF50P01)
- 2 bar $\pm 10\%$ (DLE20VF50P01)
- 5 bar $\pm 10\%$ (DLE50VF50P01)
- 7 bar $\pm 10\%$ (DLE70VF50P01)
- 9,5 bar $\pm 10\%$ (DLE95VF50P01)

Electrical/Visual Differential Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: FPM


Technical data:

- Indicator type: Electrical/Visual differential indicator
- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25 °C to +110 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Resistive load: 5 A / 250 VAC
- Thermal lockout setting: +30 °C
- Electrical connections: 50 - EN 175301-803
- Protection degree: IP 65 in according to EN 60529

HYDRAULIC SYMBOL




ELECTRICAL SYMBOL



DIFFERENTIAL INDICATORS

DTA



Available setting:
 1,2 bar $\pm 10\%$ (DTA12xF70P01)
 2 bar $\pm 10\%$ (DTA20xF70P01)
 5 bar $\pm 10\%$ (DTA50xF70P01)
 7 bar $\pm 10\%$ (DTA70xF70P01)
 9,5 bar $\pm 10\%$ (DTA95xF70P01)

Electronic Differential Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: NBR


Technical data:

- Indicator type: Electronic differential indicator
- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25°C to $+110^{\circ}\text{C}$
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943


Electrical data:

- Power supply: 24 VDC
- Analogue output: From 4 to 20 mA
- Thermal lockout: 30°C (all output signals stalled up to 30°C)
- Protection degree: IP 67 in according to EN 60529


HYDRAULIC SYMBOL



ELECTRICAL SYMBOL



DVA



Available setting:
 1,2 bar $\pm 10\%$ (DVA12xP01)
 2 bar $\pm 10\%$ (DVA20xP01)
 5 bar $\pm 10\%$ (DVA50xP01)
 7 bar $\pm 10\%$ (DVA70xP01)
 9,5 bar $\pm 10\%$ (DVA95xP01)

Visual Differential Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: HNBR - FPM


Technical data:

- Indicator type: Visual differential indicator
- Reset: Automatic reset
- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25°C to $+110^{\circ}\text{C}$
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943

HYDRAULIC SYMBOL



DVM



Available setting:
 1,2 bar $\pm 10\%$ (DVM12xP01)
 2 bar $\pm 10\%$ (DVM20xP01)
 5 bar $\pm 10\%$ (DVM50xP01)
 7 bar $\pm 10\%$ (DVM70xP01)
 9,5 bar $\pm 10\%$ (DVM95xP01)

Visual Differential Indicator

Materials:

- Body: Brass
- Internal parts: Brass - Nylon
- Seals: HNBR - FPM

Technical data:

- Indicator type: Visual differential indicator
- Reset: Manual reset
- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25°C to $+110^{\circ}\text{C}$
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC fluids in according to ISO 2943

HYDRAULIC SYMBOL



Ordering information DE - DL - DV

Series DE

Example:

1	2	3	4	5	6	7
DE	A	20	H	A	50	P01

Series DL

Example:

1	2	3	4	5	6	7
DL	A	20	H	A	52	P01

Series DT

Example:

1	2	3	4	5	6	7
DT	A	20	H	F	70	P01

Series DV

Example:

1	2	3	4	7
DV	A	20	H	P01

Series T2

Example:

1	4
T2	F

1 - Series

DE	Electrical indicator
DL	Electrical/Visual indicator
DT	Electronic indicator
DV	Visual indicator
T2	Indicator plug

2 - Type

DE series

A	Standard type
M	With wired connector

DL series

A	Standard type
E	Standard type for High power supply

DT series

A	Standard type
------------------------	---------------

DV series

A	Automatic reset
M	Manual reset

3 - Setting pressure

12	1,5 bar
20	2 bar
50	5 bar
70	7 bar
95	9,5 bar

4 - Seals

H	HNBR
	On request

5 - Thermostat (excluded for DV)

A	Without thermostat
F	With thermostat (Normally open up to 30°C) Option available only for DEM-DTA series

6 - Electrical connection (excluded for BV)

DEA - DLE series

50	EN 175301-803 connector
-------------------------	-------------------------

DEM series

10	AMP Superseal series 1,5 (Normally open contacts)
20	AMP Timer Junior (Normally open contacts)
30	Deutsch DT-04-2-P (Normally open contacts)
35	Deutsch DT-04-3-P (Change over contacts)
	On request

DLX series

51	EN 175301-803 clear connector with 24 V lamps
52	EN 175301-803 clear connector with 110 V lamps
71	M12 IEC 61076-2-101 clear connector with 24 V lamps

DTA series

70	M12 IEC 61076-2-101 connector
-------------------------	-------------------------------

7 - Option

P01	MP Filtri standard
Pxx	Customer request

MP Filtri - The filter functions as described in this bulletin are valid exclusively for original MP Filtri filter elements and replacement parts. All rights reserved.

The data in this publication are purely guideline. MP Filtri reserves the right to make changes to the models described herein at any time it deems fit in relation to technical or commercial requirements.
The colours of the products shown on the cover are purely guideline. Copyright. All rights reserved.