




GP

EXTERNAL GEAR PUMPS

SERIES 20

OPERATING PRINCIPLE




TECHNICAL SPECIFICATIONS

GP PUMP SIZE		GP1	GP2	GP3
Displacement range	cm ³ /rev	1.3 ÷ 9.1	7 ÷ 27.9	20.7 ÷ 87.6
Flow rate and operating pressures		see table 3 - Performances		
Rotation speed		see table 3 - Performances		
Rotation direction		clockwise, anticlockwise or reversible (seen from the shaft side)		
Loads on the shaft		radial and axial load are not allowed		
Max torque applicable to the shaft		see paragraph 14.1		
Hydraulic connection		flanged fittings (see paragraph 16)		
Type of mounting		4 hole flange - rectangular type		
Mass: standard version version H	kg	1.2 ÷ 1.6 1.9 ÷ 2.3	2.6 ÷ 3.5 3.8 ÷ 4.7	6 ÷ 8.5 8.7 ÷ 11.2

Ambient temperature range	°C	-20 / +50
Fluid temperature range	°C	-15 / +80
Fluid viscosity range	see paragraph 2.2	
Fluid contamination degree	see paragraph 2.3	
Recommended viscosity	cSt	25 ÷ 100

HYDRAULIC SYMBOL



1 - IDENTIFICATION CODE

1.1 - Identification code for single and front pumps

G	P			-						/	20	N	
----------	----------	--	--	----------	--	--	--	--	--	----------	-----------	----------	--

External gear pump

Pump size: _____
1 = from 1,3 to 9,1 cm³/rev
2 = from 7,0 to 27,9 cm³/rev
3 = from 20,7 to 87,6 cm³/rev

omit for single pumps (**standard**)
F = only for front pump to be coupled

Nominal size _____
 (see table 3 - Performances)

Rotation direction (seen from the shaft side) _____
R = clockwise (**standard**) **L** = anticlockwise
D = reversible (option available for single pumps only)

Mounting flange _____
9 = 4 hole - rectangular type (**standard**)
0 = SAE J744 - 2 hole

H = version for high pressures.
 Omit for standard pressure.

Seals:
N = NBR seals for mineral oils

Series No. (from 20 to 29 sizes and mounting dimensions remain unchanged)

Hydraulic connection
F = flanged ports (**standard**)
B = BSP threaded ports
U = UNF threaded ports

Type of shaft - see **NOTE 1**
7 = tapered with key (**standard**)
5 = cylindrical with key (available for single pumps only)
0 = cylindrical with key SAE-J744
1 = SAE-J744 splined

NOTE 1: See at table 1.4 compatibility among mounting flange, type of shaft and type of hydraulic connection

1.2 - Identification code for intermediate and rear pumps

G	P			-						/	20	N	
----------	----------	--	--	----------	--	--	--	--	--	----------	-----------	----------	--

External gear pump

Pump size: _____
1 = from 1,3 to 9,1 cm³/rev
2 = from 7,0 to 27,9 cm³/rev
3 = from 20,7 to 87,6 cm³/rev

Pump position: _____
M = Intermediate
R = Rear

Nominal size _____
 (see table 3 - Performances)

Rotation direction (seen from the shaft side) _____
R = clockwise (**standard**) **L** = anticlockwise

H = version for high pressures.
 Omit for standard pressure.

Seals:
N = NBR seals for mineral oils

Series No. (from 20 to 29 sizes and mounting dimensions remain unchanged)

Hydraulic connection
F = flanged ports (**standard**)
B = BSP threaded ports
U = UNF threaded ports

NOTE 2: Front, intermediate or rear pumps for multiple groups are supplied without mating joint, which must be ordered separately (see paragraph 1.5). To order a group of one or more pumps completely assembled see paragraph 1.3.

1.3 - Identification code for multiple pumps

identification code front pump + identification code intermediate pump (omit for double pumps) + identification code rear pump

1.4 - Compatibility among mounting flange, type of shaft and type of hydraulic connection

FLANGE CODE	SHAFT CODE				HYDRAULIC CONNECTION CODE		
	7	5	0	1	F	B	U
9	yes	yes	no	no	yes	yes	no
0	no	no	yes	yes	yes	no	yes

1.5 - Identification code for mating joints

FIRST PUMP	SECOND PUMP		
	GP1	GP2	GP3
GP1	3101100003	-	-
GP2	3101100004	3101100005	-
GP3	3101100006	3101100007	3101100008

1.6 - Examples

a) single pump size 1 - 1,3 cm³/rev - anticlockwise rotation - standard flange and shaft

GP1-0013L97F/20N

b) single pump size 2 - 14 cm³/rev - clockwise rotation - standard flange and shaft

GP2-0140R97F/20N

c) single pump size 3 - 22,5 cm³/rev - clockwise rotation - SAE flange and shaft

GP3-0225R01F/20N

d) double pump made of: - pump size 2 - 7 cm³/rev
 - pump size 1 - 2 cm³/rev - high pressure

GP2F-0070R97F/20N + GP1R-0020RF/20NH

e) triple pump made of: - pump size 3 - 22,5 cm³/rev
 - pump size 2 - 14 cm³/rev
 - pump size 1 - 2 cm³/rev

GP3F-0225R97F/20N + GP2M-0140RF/20N + GP1R-0020RF/20N

2 - HYDRAULIC FLUID

2.1 Type of fluid

Use mineral oil based hydraulic fluids with anti-foam and antioxidant additives, in conformity with the requisites of the following standards:

- FZG test - 11th stage
- DIN 51525
- VDMA 24317

For use with other types of fluid (water glycol, phosphate esters and others), consult our technical dept. Operation with fluid at a temperature greater than 80°C causes a premature deterioration of the fluid quality and of the seals. The physical and chemical properties of the fluid must be maintained.

2.2 - Fluid viscosity

The operating fluid viscosity must be within the following range:

minimum viscosity	12 cSt	referred to the maximum fluid temperature of 80 °C
optimum viscosity	25 ÷ 100 cSt	referred to the operating temperature of the fluid in the tank
maximum viscosity	1600 cSt	limited to only the start-up phase of the pump

2.3 - Degree of fluid contamination

The maximum degree of fluid contamination must be according to ISO 4406:1999 class 20/18/15; therefore, use of a filter with $\beta_{20} \geq 75$ is recommended. A degree of maximum fluid contamination according to ISO 4406:1999 class 18/16/13 is recommended for optimum endurance of the pump. Hence, use of a filter with $\beta_{10} \geq 100$ is recommended.

If there is a filter installed on the suction line, be sure that the pressure at the pump inlet is not lower than the values specified in paragraph 13.

The suction filter must be equipped with a by-pass valve and, if possible, with a clogging indicator.

3 - PERFORMANCE RATINGS

(values obtained with mineral oil with viscosity of 36 cSt at 50°C)

PUMP SIZE	NOMINAL SIZE	DISPLACEMENT [cm3/rev]	MAX FLOW RATE (at 1500 rpm) [l/min.]	MAX OPERATING PRESSURE (at 1500 rpm) [bar]	MAX PEAK PRESSURE (at 1500 rpm) [bar]	MAX ROTATION SPEED [rpm]	MIN ROTATION SPEED [rpm]
GP1	0013	1,3	2,0	250 (270)	290 (310)	6000	800
	0020	2,0	3,0				
	0027	2,7	4,0				
	0034	3,4	5,1				
	0041	4,1	6,1				
	0051	5,1	7,6	230 (260)	260 (290)	4000	
	0061	6,1	9,1			3800	
	0074	7,4	11,1	200	230	3200	600
	0091	9,1	13,6	180	210	2600	
GP2	0070	7,0	10,5	250 (280)	290 (310)	4000	600
	0095	9,5	14,2			3000	
	0113	11,3	16,9	230 (260)	270 (300)	4000	500
	0140	14,0	21,0				
	0158	15,8	23,7	210 (260)	240 (290)	3600	
	0178	17,8	26,7				
	0208	20,8	31,2	180 (230)	210 (260)	3200	
	0234	23,4	35,1			3000	
	0279	27,9	41,8	170 (200)	200 (230)	2500	
GP3	0207	20,7	31,0	230 (280)	270 (310)	3500	500
	0225	22,5	33,7				
	0264	26,4	39,6				
	0337	33,7	50,5				
	0394	39,4	59,1	220 (260)	260 (290)	2800	400
	0427	42,7	64,0	210 (250)	250 (280)		
	0514	51,4	77,1	200 (230)	240 (260)	2400	
	0600	60,0	90,0	190	220	2800	
	0696	69,6	104,4	170	200	2500	
	0776	77,6	116,4	160	190	2300	
	0876	87,6	131,4	140	170	2000	



NOTE: The values in parentheses refer to the version **H**, for high pressures.

4 - CURVES AND CHARACTERISTIC DATA OF GROUP GP1 PUMPS

(values obtained with mineral oil with viscosity of 36 cSt at 50°C)

4.1 - Flow rate curves $Q=f(n)$ obtained with operating pressure 0 bar

Q [l/min]



4.2 - Efficiencies

PUMP NOMINAL SIZE	VOLUMETRIC EFFICIENCY [%]	TOTAL EFFICIENCY [%]
0013	0,90	0,82
0020	0,90	0,85
0027	0,95	0,90
0034	0,91	0,87
0041	0,94	0,90
0051	0,96	0,92
0061	0,96	0,92
0074	0,96	0,90
0091	0,96	0,88

The volumetric and total efficiencies for the various nominal dimensions of the Group GP1 pumps, measured at 1500 rpm and with 150 bar operating pressure, are shown in the table.










The total efficiency considers the volumetric efficiency and the mechanical efficiency of the pump in the specified operating conditions.

4.3 - Noise level

PUMP NOMINAL SIZE	NOISE LEVEL [dB (A)]
0013	65
0020	66
0027	68
0034	68
0041	70
0051	73
0061	73
0074	73
0091	77

The noise levels for the various nominal dimensions of the Group GP1 pumps, measured at 1500 rpm, with 150 bar operating pressure and measured at a distance of 1 metre from the pump, are shown in the table.



4.4 - Absorbed power curves $N=f(n)$, measured with operating pressures from 50 to 250 bar



5 - CURVES AND CHARACTERISTIC DATA OF GROUP GP2 PUMPS

(values obtained with mineral oil with viscosity of 36 cSt at 50°C)

5.1 - Flow rate curves $Q=f(n)$ obtained with operating pressure 0 bar



5.2 - Efficiencies

PUMP NOMINAL SIZE	VOLUMETRIC EFFICIENCY [%]	TOTAL EFFICIENCY [%]
0070	0,92	0,87
0095	0,95	0,88
0113	0,95	0,87
0140	0,93	0,87
0158	0,95	0,86
0178	0,93	0,85
0208	0,93	0,88
0234	0,97	0,89
0279	0,94	0,85

The volumetric and total efficiencies for the various nominal dimensions of the Group GP2 pumps, measured at 1500 rpm and with 150 bar operating pressure, are shown in the table.










The total efficiency considers the volumetric efficiency and the mechanical efficiency of the pump in the specified operating conditions.

5.3 - Noise level

PUMP NOMINAL SIZE	NOISE LEVEL [dB (A)]
0070	75
0095	77
0113	77
0140	72
0158	72
0178	73
0208	74
0234	76
0279	76

The noise levels for the various nominal dimensions of the Group GP2 pumps, measured at 1500 rpm, with 150 bar operating pressure and measured at a distance of 1 metre from the pump, are shown in the table.



5.4 - Absorbed power curves $N=f(n)$, measured with operating pressures from 50 to 250 bar



6 - CURVES AND CHARACTERISTIC DATA OF GROUP GP3 PUMPS

(values obtained with mineral oil with viscosity of 36 cSt at 50°C)

6.1 - Flow rate curves $Q=f(n)$ obtained with operating pressure 0 bar



6.2 - Efficiencies

PUMP NOMINAL SIZE	VOLUMETRIC EFFICIENCY [%]	TOTAL EFFICIENCY [%]
0207	0,88	0,83
0225	0,97	0,92
0264	0,90	0,84
0337	0,92	0,87
0394	0,91	0,86
0427	0,92	0,82
0514	0,93	0,83
0600	0,85	0,82
0696	0,95	0,90
0776	0,93	0,87
0876	0,89	0,84

The volumetric and total efficiencies for the various nominal dimensions of the Group GP3 pumps, measured at 1500 rpm and with 150 bar operating pressure, are shown in the table.












The total efficiency considers the volumetric efficiency and the mechanical efficiency of the pump in the specified operating conditions.

6.3 - Noise level


PUMP NOMINAL SIZE	NOISE LEVEL [dB (A)]
0207	75
0225	75
0264	76
0337	72
0394	72
0427	73
0514	75
0600	77
0696	77
0776	76
0876	78

The noise levels for the various nominal dimensions of the Group GP3 pumps, measured at 1500 rpm, with 150 bar operating pressure and measured at a distance of 1 metre from the pump, are shown in the table.


6.4 - Absorbed power curves $N=f(n)$, measured with operating pressures from 50 to 250 bar



7 - GROUP GP1 PUMPS OVERALL AND MOUNTING DIMENSIONS WITH STANDARD FLANGE




8 - GROUP GP1 PUMPS OVERALL AND MOUNTING DIMENSIONS WITH SAE FLANGE




9 - GROUP GP2 PUMPS OVERALL AND MOUNTING DIMENSIONS WITH STANDARD FLANGE

dimensions in mm




tapered shaft end
(standard, id. code **7**)



cylindrical with key shaft end
(id code: 5)

NOTE:


1. On pumps with anticlockwise rotation the ports (1) and (2) are reversed
2. On reversible pumps the delivery port has the same size of the suction




pump nominal dimension	L	M	1 suction port clockwise rotation		2 delivery port clockwise rotation	
			flange	BSP	flange	BSP
0070	47,5	97,5	Ø13	1/2"	Ø13	1/2"
0095	49,5	101,5				
0113	51	104,5	Ø19	3/4"		
0140	53	108,5				
0158	54,5	111,5				
0178	56	114,5				
0218	58,5	119,5				
0234	60,5	123,5		Ø19		
0279	64	130,5				

10 - GROUP GP2 PUMPS OVERALL AND MOUNTING DIMENSIONS WITH SAE FLANGE

dimensions in mm




splined shaft end
SAE J744 6/32 d.p. - 9
(standard, id. code 1)



cylindrical shaft end
SAE J744
(id. code: 0)


NOTE:

1. On pumps with anticlockwise rotation the ports (1) and (2) are reversed
2. On reversible pumps the delivery port has the same size of the suction




Pump nominal dimension	L	M	1 suction port clockwise rotation		2 delivery port clockwise rotation	
			flange	UNF	flange	UNF
0070	47,5	97,5	Ø 13	11/16" 12 UNF	Ø 13	7/8" 14 UNF
0095	49,5	101,5				
0113	51	104,5				
0140	53	108,5				
0158	54,5	111,5				
0178	56	114,5	Ø 19			
0208	58,5	119,5				
0234	60,5	123,5				
0279	64	130,5				
				Ø 19		

11 - GROUP GP3 PUMPS OVERALL AND MOUNTING DIMENSIONS WITH STANDARD FLANGE



12 - GROUP GP3 PUMPS OVERALL AND MOUNTING DIMENSIONS WITH SAE FLANGE



13 - INSTALLATION

- The GP gear pumps can be installed with the shaft oriented in any position.
- Be sure the control rotation direction corresponds to the direction of the arrow marked on the pump before putting the pump into operation.
- **Before starting, the pump body has to be filled with the fluid.**
- It is necessary to vent the air from the delivery connection before operating it the first time.
- The pump start up, especially at a cold temperature, should occur with the pump unloading.
- The suction line must be suitably sized to facility the flow of the oil. Bends and restrictions or an excessive line length can impede correct operation of the pump. It is advisable that the speed of 1 ÷ 2 m/sec is not exceeded in the suction line.
- The minimum suction pressure allowed is -0,3 bar relative. The pumps can not function with suction pressure.
- The gear pumps must not operate with a rotation rating of less than the minimum rotation speed (see table 3 - performance ratings). They must be filled with the same plant operation oil before installation. Filling is done through the connection lines. If necessary, rotate the pump manually.
- The motor-pump connection must be carried out directly with a flexible coupling able to compensate any offsets. Couplings that generate axial or radial loads on the pump shaft are not allowed.

14 - MULTIPLE PUMPS

The possibility to couple several pumps makes it possible to create multi-flow groups with independent hydraulic circuits.

While sizing coupled pumps, it is necessary to make reference to the following conditions:

- The coupling can be carried out between pumps with the same dimensions or to a size of decreasing order.
- The max. rotation speed is determined by the pump with the lowest speed.
- The values of the max. applicable torque can not be exceeded.

14.1 - Maximum applicable torque

The input torque (M) for each pump is given by the following ratio:

$$M = \frac{9550 \cdot N}{n} = [\text{Nm}] \quad n = \text{rotation speed [rpm]}$$

where the absorbed power (N) is given by:

$$N = \frac{Q \cdot \Delta p}{600 \cdot \eta_{\text{tot}}} = [\text{kW}] \quad \begin{aligned} Q &= \text{flow rate [l/min]} \\ \Delta p &= \text{differential pressure between the pump suction and delivery [bar]} \\ \eta_{\text{tot}} &= \text{total efficiency (see diagrams in par. 4.2 - 5.2 - 6.2).} \end{aligned}$$


or it can be obtained from the diagrams ABSORBED POWER (see paragraphs 4.4 - 5.4 - 6.4).

If several pumps are coupled, the torque of each single pump has to be added to the torque of subsequent pumps when they are loaded simultaneously.

The obtained torque value for each pump has to be lower than the value specified in the table below.

If the obtained torque values are higher than the ones stated in the table, it is necessary to reduce the working pressure value or to replace the overloaded pump with a pump suitable to bear the required torque.

	MAX TORQUE APPLICABLE TO THE SHAFT OF THE FRONT PUMP [Nm]			MAX APPLICABLE TORQUE [Nm] (not simultaneously to the front pump)		
FRONT PUMP SIZE	tapered shaft with key code 7	SAE J744 splined shaft code 1	SAE J744 cylindrical shaft cod. 0	PUMP TO BE MATED		
				GP1	GP2	GP3
GP1	100	100	60	50	-	-
GP2	200	185	140		100	
GP3	300	600	450			220

15 - MULTIPLE PUMPS OVERALL DIMENSIONS



dimensions in mm

PUMP SIZE	NOMINAL SIZE	FRONT PUMP		REAR PUMP	
		H	K	A	B
GP1	0013	86	40	86,5	46
	0020	88	41	88,5	47
	0027	90	42	90,5	48
	0034	92	43	92,5	49
	0041	94	44	94,5	50
	0051	97	45,5	97,5	51,5
	0061	100	47	100,5	53
	0074	104	49	104,5	55
GP2	0091	109	51,5	109,5	57,5
	0070	101	47,5	103,5	53,5
	0095	105	49,5	107,5	55,5
	0113	108	51	110,5	57
	0140	112	53	114,5	59
	0158	115	54,5	117,5	60,5
	0178	118	56	120,5	62
	0208	123	58,5	125,5	64,5
	0234	127	60,5	129,5	66,5
	0279	134	64	136,5	70
GP3	0207	135,5	64	137	71,5
	0225	136,5	64,5	138	72
	0264	139,5	66	141	73,5
	0337	144,5	68,5	146	76
	0394	148,5	70,5	150	78
	0427	151,5	72	153	79,5
	0514	157,5	75	159	82,5
	0600	163,5	78	165	85,5
	0696	170,5	81,5	172	89
	0776	175,5	84	177	91,5
	0876	181,5	87	183	94,5

NOTE: For the dimensions of groups composed of three or more pumps, please consult our Technical Dept.

16 - CONNECTION FLANGES

dimensions in mm



ALUMINIUM FLANGES TYPE RP

Fastening bolt and O-rings included

	Flange code	Flange description	p_{max} [bar]	$\varnothing A$	B	C	$\varnothing D$	E	F	G	(1) SHC bolts	(2) seals
GP1	0610506	RP1 - 38	180	3/8" BSP	30	6,5	12,5	30	26	18	n°3 - M6x35	OR 121 (15.88x2.62)
	0610248	RP1 - 12		1/2" BSP	30	6,5	12,5	30	26	18		
GP2	0610508	RP2 - 12		1/2" BSP	40	8,5	18,5	40	31	20	n°3 - M8x45	OR 130 (22.22x2.62)
	0610249	RP2 - 34		3/4" BSP	40	8,5	18,5	40	31	20		
GP3	0610717	RP3 - 34		3/4" BSP	51	10,5	25	46	43	26	n°3 - M10x60	OR 4118 (29.75x3.53)
	0610250	RP3 - 100		1" BSP	56	10,5	25	46	43	26		

STEEL FLANGES TYPE RPA

	Flange code	Flange description	p_{max} [bar]	$\varnothing A$	B	C	$\varnothing D$	E	F	G	(1) SHC bolts	(2) seals
GP1	0771048	RPA1 - 38	315	3/8" BSP	30	6,5	12	24	17	9,5	n°3 - M6x20	OR 121 (15.88x2.62)
	0771049	RPA1 - 12		1/2" BSP	30	6,5	12	24	17	9,5		
GP2	0771050	RPA2 - 12		1/2" BSP	40	8,5	20	36	22	11,5	n°3 - M8x25	OR 132 (23.81x2.62)
	0770615	RPA2 - 34		3/4" BSP	40	8,5	20	36	22	11,5		
GP3	0771051	RPA3 - 34A		3/4" BSP	51	10,5	24	46	26	13	n°3 - M10x30	OR 3125 (31.42x2.62)
	0770617	RPA3 - 100A		1" BSP	51	10,5	24	46	26	13		
	0770618	RPA3 - 34B		3/4" BSP	56	10,5	24	46	26	13		
	0770619	RPA3 - 100B		1" BSP	56	10,5	24	46	26	13		
	0771052	RPA35 - 114A		1" 1/4 BSP	62	13	31	55	35	17	n°3 - M10x35	

DIPLOMATIC
OLEODINAMICA

DIPLOMATIC OLEODINAMICA S.p.A.
20015 PARABIAGO (MI) • Via M. Re Depaolini 24
Tel. +39 0331.895.111
Fax +39 0331.895.339
www.diplomatic.com • e-mail: sales.exp@diplomatic.com