




LI2241

LI0132--K-00KNPKG/US/WHG



Level sensors



1: Programming buttons



Product characteristics

Binary leakage sensor

Quick disconnect

gold-plated contacts

Approval to the German Federal Water Act WHG section 19 (building authority approval: Z-65.40-506)

Probe length: L = 132 mm

1 switching output

Application

Application	Hydrous coolants, oils, water, media similar to water
Recommended media	Hydrous coolants, oils, water, media similar to water
Cannot be used for:	granulates and bulk materials, acids and alkalis, hygienic and electroplating applications
Dielectric constant medium	> 1.8
Medium temperature oil [°C]	0...65
Medium temperature water and hydrous media [°C]	0...35

Electrical data

Electrical design	DC PNP
Operating voltage [V]	10...36 DC *)
Current consumption [mA]	22 (24 V)
Protection class	III
Reverse polarity protection	yes

Outputs

Output	1 switching output
Output function	normally closed
Current rating [mA]	200
Voltage drop [V]	< 2.5
Short-circuit protection	yes (non-latching)
Overload protection	yes

Measuring / setting range

Probe length L [mm]	132
Active range A [mm]	31

Environment

Ambient temperature [°C]	0...65
Maximum vessel pressure [bar]	+/- 0.5 (mounted with mounting accessories E43001 - E43007)
Protection	IP 65 / IP 67

Tests / approvals



LI2241

LI0132--K-00KNPKG/US/WHG



Level sensors

Approval	WHG § 19	
EMC	EN 61000-6-2 EN 61000-6-4	: 2005 + corr. 2005 : 2007
Shock resistance	DIN EN 60068-2-29:	12 g (11 ms)
Vibration resistance	DIN EN 60068-2-6	5 g (10...2000 Hz)
MTTF [Years]	608	

Mechanical data

Materials (wetted parts)	PP	
Housing materials	PP GF30; TPE-U	
Weight [kg]	0.162	


Displays / operating elements

Display	Power LED green Switching status LED yellow
---------	--

Electrical connection

Connection	M12 connector; gold-plated contacts
------------	-------------------------------------

Wiring



Remarks

Remarks	*) cULus - Class 2 source required
---------	------------------------------------

Pack quantity [piece]	1
-----------------------	---