




PP004E

PP-010-RBG14-QFPKG/US/ IV



Pressure sensors



- 1: ventilation
- 2: sealing FPM / DIN 3869-14



Product characteristics

Electronic pressure sensor

Quick disconnect

Adjustment of the switch point by teach function

E1 type approval

Process connection: G 1/4 A / M5 I

2 outputs

OUT1 = switching output

OUT2 = switching output or diagnostic output

Measuring range: -1...10 bar / -14.5...145 psi / -0.1...1.0 MPa

Application

Application	Type of pressure: relative pressure Liquids and gases		
Pressure rating	75 bar	1087 psi	7.5 MPa
Bursting pressure min.	150 bar	2175 psi	15 MPa
Medium temperature [°C]	-25...90		

Electrical data

Electrical design	DC PNP
Operating voltage [V]	9.6...36 DC ¹⁾
Current consumption [mA]	< 45
Insulation resistance [MΩ]	> 100 (500 V DC)
Protection class	III
Reverse polarity protection	yes

Outputs

Output	2 outputs OUT1 = switching output OUT2 = switching output or diagnostic output
Output function	2 x normally open / closed programmable or 1 x normally open / closed programmable + 1 x normally closed (diagnostic function)
Current rating [mA]	2 x 250
Voltage drop [V]	< 2
Short-circuit protection	yes (non-latching)
Overload protection	yes



PP004E

PP-010-RBG14-QFPKG/US/ /V



Pressure sensors

Switching frequency [Hz]	170
--------------------------	-----

Measuring / setting range

Measuring range	-1...10 bar	-14.5...145 psi	-0.1...1.0 MPa
Setting range			
Set point, SP	-0.90...10.00 bar	-13...145 psi	-0.090...1.000 MPa
Reset point, rP	-0.95...9.95 bar	-14...144 psi	-0.095...0.995 MPa
in steps of	0.05 bar	1 psi	0.005 MPa
Factory setting	SP1 = 2.50 bar; rP1 = 2.30 bar SP2 = 7.50 bar; rP2 = 7.30 bar OUT1 = Hno; OUT2 = Hno		

Accuracy / deviations

Accuracy / deviations (in % of the span)	
Switch point accuracy	< ± 0.5
Characteristics deviation *)	< ± 0.25 (BFSL) / < ± 0.5 (LS)
Hysteresis	< ± 0.1
Repeatability **)	< ± 0.1
Long-term stability ***)	< ± 0.1
Temperature coefficients (TEMPCO) in the temperature range 0...80° C (in % of the span per 10 K)	
Greatest TEMPCO of the zero point	0.2
Greatest TEMPCO of the span	0.2

Reaction times

Power-on delay time [s]	0.3
Min. response time switching output [ms]	3
Damping for the switching output (dAP) [s]	0.003 - 0.006 - 0.010 - 0.017 - 0.060 - 0.125 - 0.250 - 0.500

Interfaces

IO-Link Device	
Transfer type	COM2 (38.4 kBaud)
IO-Link revision	1.0
IO-Link Device ID	6 d / 00 00 06 h
Profiles	no profile
SIO mode	yes
Required master port class	A
Process data analogue	1
Process data binary	2
Min. process cycle time [ms]	2.3

Environment

Ambient temperature [°C]	-25...85
Storage temperature [°C]	-40...100
Protection	IP 68 ****) / IP 69K

Tests / approvals

EMC	noise immunity	according to EN 61000-6-2 4 kV contact discharge / 15 kV air discharge
	EN 61000-4-2 ESD:	20 V/m
	EN 61000-4-3 HF radiated:	20 V/m
	EN 61000-4-4 Burst:	4 kV coupling clamp



PP004E

PP-010-RBG14-QFPKG/US/ /V

Pressure sensors

	EN 61000-4-5 Surge: EN 61000-4-6 HF conducted: noise immunity Absorber chamber test to ISO 11452-2: EN 50155:	0.5 kV supply / 1 kV signal for DC units 10 V according to the automotive directive 95/54/EC / 04/104EC / 05/83/EC 80 V/m class T3, C1, S1
Shock resistance	DIN IEC 60068-2-27 / DIN IEC 60068-2-29: DIN EN 61373:	1000 g Category 3
Vibration resistance	DIN IEC 68-2-6: DIN EN 60068-2-64 DIN EN 61373:	20 g (10...2000 Hz) 14 g Category 2
MTTF [Years]		310

Mechanical data

Process connection	G ¼ A / M5 I
Materials (wetted parts)	stainless steel (303S22); ceramics; FPM (Viton)
Housing materials	stainless steel (304S15); FPM (Viton); EPDM/X (Santoprene); PA
Switching cycles min.	100 million
Weight [kg]	0.226

Displays / operating elements


Display	Power 2 x LED green Switching status 2 x LED yellow
---------	--

Electrical connection

Connection	M12 connector
------------	---------------

Wiring

-----OUT1/Teach/Data-----
data channel for bidirectional communication
in addition:
switching signal for pressure limit value or input for teach signal
-----OUT2-----
switching signal for pressure limit value or diagnostic signal



Remarks

Remarks	1) supply voltage for communication mode: 18...32 V DC referring to UL: "limited voltage" with overcurrent protection in accordance with UL508 *) BFSL = Best Fit Straight Line / LS = Limit Value Setting **) with temperature fluctuations < 10 K ***) in % of the span per year ****) 7 days / 1 m water depth / 0.1 bar
---------	---

Pack quantity [piece]	1
-----------------------	---