




PT5502

PT-100-SEG14-A-ZVG/US



Pressure sensors



1: Process connection sealing HNBR / DIN 3869



Product characteristics

Electronic pressure sensor

M12 connector

for mobile applications

E1 compliant

Process connection: G 1/4 A (according to DIN EN ISO 1179-2)

Analog output

Measuring range: 0...100 bar

Application

Application

Type of pressure: relative pressure
Group 2 fluids according to the Pressure Equipment Directive (PED),
group 1 fluids on request

Pressure rating

[bar]

250 (static)

Bursting pressure min.

[bar]

1000

Vacuum resistance

[mbar]

-1000

Medium temperature

[°C]

-40...125

Electrical data

Electrical design

DC

Operating voltage

[V]

8...32 DC

Insulation resistance

[MΩ]

> 100 (500 V DC)

Protection class

III

Reverse polarity protection

yes

Outputs

Output

Analog output

Output function

4...20 mA analog

Short-circuit proof

yes

Overload protection

yes

Max. load

[Ω]

(U_b - 8 V) / 0.02 A

Min. load

[Ω]

(U_b - 24 V) / 0.02 A



PT5502

PT-100-SEG14-A-ZVG/US



Pressure sensors

Characteristic load curve current output



1: Max. load; 2: Min. load

Measuring / setting range

Measuring range [bar] 0...100

Accuracy / deviations

Accuracy / deviations (in % of the span)

Characteristics deviation *) < ± 0.8

Linearity < ± 0.25 (BFSL) / < ± 0.5 (LS)

Hysteresis < ± 0.2

Repeatability **) < ± 0.05

Long-term stability ***) < ± 0.1

Temperature coefficients (TEMPCO) in the temperature range -40...125° C (in % of the span per 10 K)

Greatest TEMPCO of the zero point < ± 0.1 (0...80 °C); < ± 0.2 (-40...0 °C / 80...125 °C)

Greatest TEMPCO of the span < ± 0.1 (0...80 °C); < ± 0.2 (-40...0 °C / 80...125 °C)

Reaction times

Step response time analogue output [ms] 2

Environment

Ambient temperature [°C] -40...100

Storage temperature [°C] -40...100

Protection IP 67 / IP 69K

Tests / approvals

Pressure equipment directive sound engineering practice

EMC
Conforms to UN ECE 10 rev. 4
ISO 11452-2 30 V/m
DIN EN 61326-1

Shock resistance DIN EN 60068-2-27 500 g (1 ms)

Vibration resistance DIN EN 60068-2-6 20 g (10...2000 Hz)

MTTF [Years] 704

Mechanical data

Process connection G ¼ A (according to DIN EN ISO 1179-2)

Process connection sealing HNBR (to DIN 3869)

Materials (wetted parts) 1.4542 (17-4 PH / 630)²

Housing materials 1.4542 (17-4 PH / 630)²; stainless steel (316L / 1.4404); PEI

Min. pressure cycles 60 millions in the course of the lifetime (at 1.2 times the nominal pressure)

Tightening torque [Nm] 25...35 (recommended tightening torque¹)

Restrictor element integrated yes



PT5502

PT-100-SEG14-A-ZVG/US

Pressure sensors

Weight	[kg]	0.058
--------	------	-------


Electrical connection

Connection	M12 connector
------------	---------------

Max. cable length	[m]	30
-------------------	-----	----

Wiring

Core colors
 BN brown
 WH white



OUT: 4...20 mA
 Colours to DIN EN 60947-5-2

Remarks

Remarks	<p>*) incl. drift when overtightened, zero point and span error, non-linearity, hysteresis **) with temperature fluctuations < 10 K ***) in% of the span / 6 months 1) Depends on lubrication, seal and pressure rating 2) Characteristics similar to stainless steel (e.g. 304/1.4301) but higher strength. BFSL = Best Fit Straight Line / LS = Limit Value Setting</p>
---------	---

Pack quantity	[piece]	1
---------------	---------	---