


**PT9551**

PT-250-SBG14-B-DVG/US/ IW

Pressure sensors



1: FKM seal / DIN 3869-14  
tightening torque 25 Nm



**Product characteristics**

Electronic pressure sensor

for mobile applications

e1 compliant

Process connection: G 1/4 A

Analog output

Measuring range: 0...250 bar

**Application**

Application	Type of pressure: relative pressure Liquids and gases
Pressure rating [bar]	400
Bursting pressure min. [bar]	1000
Medium temperature [°C]	-25...90 ****)

**Electrical data**

Electrical design	DC
Operating voltage [V]	16...36 DC
Current consumption [mA]	< 6
Insulation resistance [MΩ]	> 100 (80 V DC)
Protection class	III
Reverse polarity protection	yes

**Outputs**

Output	Analog output
Output function	0...10 V analog
Analog output	0...10 V
Max. load [Ω]	min. 2000

**Measuring / setting range**

Measuring range [bar]	0...250
-----------------------	---------

**Accuracy / deviations**

Accuracy / deviations (in % of the span)	
Characteristics deviation *)	< ± 1.0
Linearity	< ± 0.25 (BFSL) / < ± 0.5 (LS)
Hysteresis	< ± 0.2

**PT9551**

PT-250-SBG14-B-DVG/US/ IW

Pressure sensors

Repeatability **)	< ± 0.1
Long-term stability ***)	< ± 0.1
Temperature coefficients (TEMPCO) in the temperature range -25...90° C (in % of the span per 10 K)	
Greatest TEMPCO of the zero point	< ± 0.1
Greatest TEMPCO of the span	< ± 0.1

**Reaction times**

Step response time analogue output [ms]	8
-----------------------------------------	---

**Environment**

Ambient temperature [°C]	-25...90 ****)
Storage temperature [°C]	-40...100
Protection	IP 67 / IP 69K

**Tests / approvals**

EMC	EN 61000-4-2 ESD: noise immunity ISO 11452-2 ISO 11452-4 ISO 7637-2 radiation of interference EN 61000-6-1 EN 61000-6-4	4 kV CD / 8 kV AD according to the automotive directive 95/54/EC 04/104EC / 05/83EC 100 V/m 100 mA / severity level 4 severity level 4 according to CISPR 25
Shock resistance	DIN IEC 68-2-27:	50 g (11 ms)
Vibration resistance	DIN IEC 68-2-6:	20 g (10...2000 Hz)
MTTF [Years]		1069


**Mechanical data**

Process connection	G ¼ A
Materials (wetted parts)	stainless steel 316L / 1.4404; FPM (Viton)
Housing materials	stainless steel 316L / 1.4404; TROGAMID
Min. pressure cycles	50 million
Weight [kg]	0.081

**Electrical connection**

Connection	M12 connector
------------	---------------

**Wiring**



**Remarks**

Remarks	*) incl. drift due to tightening torque, zero and span error **) with temperature fluctuations < 10 K ***) in% of the span / 6 months ****) -40...100°C upon request BFSL = Best Fit Straight Line / LS = Limit Value Setting
---------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Pack quantity [piece]	1
-----------------------	---



**PT9551**

PT-250-SBG14-B-DVG/US/ /W

**Pressure sensors**