




# PU5402

PU-100-SEG14-B-DVG/US/ /W



Pressure sensors



1: Process connection sealing FKM / DIN 3869



## Product characteristics

Electronic pressure sensor

for industrial applications

Process connection: G 1/4 A (according to DIN EN ISO 1179-2)

Analog output

Measuring range: 0...100 bar

## Application

Application

Type of pressure: relative pressure

Group 2 fluids according to the Pressure Equipment Directive (PED),  
group 1 fluids on request

Pressure rating [bar]

250 (static)

Bursting pressure min. [bar]

1000

Vacuum resistance [mbar]

-1000

Medium temperature [°C]

-40...90

## Electrical data

Electrical design

DC

Operating voltage [V]

16...36 DC

Current consumption [mA]

< 12

Insulation resistance [MΩ]

> 100 (500 V DC)

Protection class

III

Reverse polarity protection

yes

## Outputs

Output

Analog output

Output function

0...10 V analog

Short-circuit proof

yes

Overload protection

yes

Min. load resistance [Ω]

2000

## Measuring / setting range

Measuring range

[bar]

0...100

## Accuracy / deviations

Accuracy / deviations  
(in % of the span)

Characteristics deviation \*)

< ± 0.5

Linearity

< ± 0.1 (BFSL) / < ± 0.2 (LS)

Hysteresis

< ± 0.2

Repeatability \*\*)

< ± 0.05



# PU5402

PU-100-SEG14-B-DVG/US/ /W



Pressure sensors

Long-term stability ***)	< ± 0.1	
Temperature coefficients (TEMPCO) in the temperature range -40...90° C (in % of the span per 10 K)		
Greatest TEMPCO of the zero point + span	< ± 0.1 (-25...90 °C) / < ± 0.2 (-40...-25 °C)	
<b>Reaction times</b>		
Step response time analogue output	[ms]	1
<b>Environment</b>		
Ambient temperature	[°C]	-40...90
Storage temperature	[°C]	-40...100
Protection		IP 67 / IP 69K
<b>Tests / approvals</b>		
Pressure equipment directive		sound engineering practice
EMC		DIN EN 61000-6-2 DIN EN 61000-6-3
Shock resistance		DIN EN 60068-2-27      50 g (11 ms)
Vibration resistance		DIN EN 60068-2-6      20 g (10...2000 Hz)
MTTF	[Years]	762
<b>Mechanical data</b>		
Process connection		G 1/4 A (according to DIN EN ISO 1179-2)
Process connection sealing		FKM (to DIN 3869)
Materials (wetted parts)		1.4542 (17-4 PH / 630) <sup>2</sup>
Housing materials		1.4542 (17-4 PH / 630) <sup>2</sup> ; stainless steel (316L / 1.4404); PEI
Min. pressure cycles		60 millions in the course of the lifetime (at 1.2 times the nominal pressure)
Tightening torque	[Nm]	25...35 (recommended tightening torque <sup>1</sup> )
Restrictor element integrated		no
Weight	[kg]	0.055
<b>Electrical connection</b>		
Connection		M12 connector
<b>Wiring</b>		
Core colors		
BN	brown	2
BU	blue	1
WH	white	3
		OUT: 0...10 V Colours to DIN EN 60947-5-2
<b>Remarks</b>		
Remarks	<p>*) incl. drift when overtightened, zero point and span error, non-linearity, hysteresis          **) with temperature fluctuations &lt; 10 K          ***) in% of the span / 6 months  <sup>1</sup>) Depends on lubrication, seal and pressure rating  <sup>2</sup>) Characteristics similar to stainless steel (e.g. 304/1.4301) but higher strength.          BFSL = Best Fit Straight Line / LS = Limit Value Setting</p>	
Pack quantity	[piece]	1



**PU5402**

PU-100-SEG14-B-DVG/US/ /W



**Pressure sensors**

ifm eefector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — PU5402 — 07.09.2015