


PX9227

PA-001PRBN14-C-DVG/US/ IV

Pressure sensors



Product characteristics

Electronic pressure sensor

Quick disconnect

e1 compliant

Process connection: 1/4" NPT

Analog output

Measuring range: 0...15 psi

Application

Application	Type of pressure: relative pressure Liquids and gases	
Pressure rating [psi]	145	
Bursting pressure min. [psi]	450	
Medium temperature [°C]	-25...90	

Electrical data

Electrical design	DC	
Operating voltage [V]	10...30 DC	
Current consumption [mA]	< 18	
Insulation resistance [MΩ]	> 100 (500 V DC)	
Protection class	III	
Reverse polarity protection	yes	

Outputs

Output	Analog output	
Output function	1...5 V analog	
Overload protection	yes	
Max. load [Ω]	min. 2000	

Measuring / setting range

Measuring range [psi]	0...15	
-----------------------	--------	--

Accuracy / deviations

Accuracy / deviations (in % of the span)		
Characteristics deviation *)	< ± 0.25 (BFSL) / < ± 0.5 (LS)	
Repeatability **)	< 0.1	
Long-term stability ***)	< ± 0.05	

Temperature coefficients (TEMPCO) in the temperature range 0...80° C (in % of the span per 10 K)

PX9227

PA-001PRBN14-C-DVG/US/ /V

Pressure sensors

Greatest TEMPCO of the zero point	0.1
Greatest TEMPCO of the span	0.2

Reaction times

Step response time analogue output [ms]	3
---	---

Environment

Ambient temperature [°C]	-25...80
Storage temperature [°C]	-40...100
Protection	IP 65

Tests / approvals

EMC	EN 61000-4-2 ESD: 4 kV CD / 8 kV AD EN 61000-4-3 HF radiated: 30 V/m EN 61000-4-4 Burst: 2 kV EN 61000-4-6 HF conducted: 10 V radiation of interference according to the automotive directive 2004/104/EC / CISPR25 noise immunity according to the automotive directive 2004/104/EC / ISO 11452-2 HF radiated 100 V/m pulse resistance according to ISO7637-2 / severity level 3
Shock resistance	DIN IEC 68-2-27: 50 g (11 ms)
Vibration resistance	DIN IEC 68-2-6: 20 g (10...2000 Hz)


Mechanical data

Process connection	¼" NPT
Materials (wetted parts)	stainless steel (303S22); ceramics; FPM (Viton)
Housing materials	stainless steel 316L / 1.4404; FPM (Viton); PA; EPDM/X (Santoprene)
Min. pressure cycles	100 million
Weight [kg]	0.222

Electrical connection

Connection	M12 connector; gold-plated contacts
------------	-------------------------------------

Wiring



Remarks

Remarks	*) BFSL = Best Fit Straight Line / LS = Limit Value Setting **) with temperature fluctuations < 10 K ***) in % of value of measuring range / 6 months
---------	---

Pack quantity [piece]	1
-----------------------	---