



PY9000

PY-600-SE MFRKG/US/ IV

Pressure sensors



- 1: 4-digit alphanumeric display
- 2: LEDs (display unit / switching status)
- 3: Programming button



Product characteristics

Pressure sensor 600 bar for homogenisers
Quick disconnect
Zero and span adjustable
Function programmable
Process connection: Clamp fitting
2 outputs OUT1 = switching output OUT2 = switching output or analog output
4-digit alphanumeric display
Measuring range: 0...600 bar

Application

Application	Type of pressure: relative pressure Liquids and gases For gaseous media the application is limited to max. 25 bar
Pressure rating [bar]	800
Bursting pressure min. [bar]	1200
Medium temperature [°C]	-25...100 (145 max 1h)

Electrical data

Electrical design	DC PNP/NPN
Operating voltage [V]	20...30 DC
Current consumption [mA]	< 65
Insulation resistance [MΩ]	> 100 (500 V DC)
Protection class	III
Reverse polarity protection	yes

Outputs

Output	2 outputs OUT1 = switching output OUT2 = switching output or analog output
Output function	2 x normally open / closed programmable or 1 x normally open / closed programmable + 1 x analog (4...20 mA / 0...10 V; programmable 1:4)

PY9000

PY-600-SE MFRKG/US/ IV

Pressure sensors

Current rating	[mA]	2 x 250
Voltage drop	[V]	< 2
Short-circuit protection		yes (non-latching)
Overload protection		yes
Switching frequency	[Hz]	≤ 170
Analog output		4...20 mA / 0...10 V
Max. load	[Ω]	4...20 mA: max. (U _b - 10 V) x 50 / 0...10 V: min. 2000

Measuring / setting range

Display unit		bar, psi, MPa
Measuring range	[bar]	0...600
Setting range		
Set point, SP	[bar]	6...600
Reset point, rP	[bar]	3...597
Analog start point, ASP	[bar]	0...240
Analog end point, AEP	[bar]	150...600
in steps of	[bar]	3

Accuracy / deviations

Accuracy / deviations (in % of the span) Turn down 1:1		
Switch point accuracy		< ± 1.0
Characteristics deviation *)		< ± 1.0
Linearity		< ± 0.5
Hysteresis		< ± 1.0
Repeatability **)		< ± 0.25
Long-term stability ***)		< ± 0.25
Temperature coefficients (TEMPCO) in the temperature range 0...80° C (in % of the span per 10 K)		
Greatest TEMPCO of the zero point		< ± 0.2
Greatest TEMPCO of the span		< ± 0.2

Reaction times

Power-on delay time	[s]	0.3
Min. response time switching output	[ms]	3
Damping for the switching output (dAP)	[s]	0...4
Damping for the analog output (dAA)	[s]	0 - 0; 1 - 0; 5 - 2
Response time analog output	[ms]	3
Integrated watchdog		yes

Software / programming

Programming options	hysteresis / window function; N.O. / N.C.; output polarity; current / voltage outputs; damping; calibration of displayed values; display can be rotated / deactivated; display unit
---------------------	---

Environment

Ambient temperature	[°C]	-25...80
Storage temperature	[°C]	-40...100
Protection		IP 67

Tests / approvals

PY9000

PY-600-SE MFRKG/US/ /V

Pressure sensors

EMC	EN 61000-4-2 ESD: 4 kV CD / 8 kV AD EN 61000-4-3 HF radiated: 10 V/m EN 61000-4-4 Burst: 2 kV EN 61000-4-5 Surge: 0.5/1 kV EN 61000-4-6 HF conducted: 10 V
Shock resistance	DIN EN 60068-2-27 50 g (11 ms)
Vibration resistance	DIN EN 60068-2-6 20 g (10...2000 Hz)
MTTF [Years]	145

Mechanical data

Process connection	Clamp fitting
Materials (wetted parts)	stainless steel 316L / 1.4404; ceramics (99.9 % Al ₂ O ₃); FKM
Housing materials	stainless steel (304S15); stainless steel 316L / 1.4404; PC (Makrolon); PBT (Pocan); PA; FPM (Viton); EPDM/X (Santoprene)
Switching cycles min.	50 million
Weight [kg]	0.366

Displays / operating elements





Display	Display unit 3 x LED green Switching status 2 x LED yellow Function display 4-digit alphanumeric display Measured values 4-digit alphanumeric display
---------	--

Electrical connection

Connection	M12 connector; gold-plated contacts
------------	-------------------------------------

Wiring

Programming of the output function (OUT1 / OUT2):
 Hno = hysteresis / normally open
 Hnc = hysteresis / normally closed
 Fno = window function / normally open
 Fnc = window function / normally closed
 Complementary outputs:
 output 1: = Hno, output 2: = Hnc
 (with the same SP / rP)



Programming of the analog output (OUT2):
 I = current output (4...20 mA)
 U = voltage output (0...10 V)



Remarks

Remarks	*) linearity, incl. hysteresis and repeatability; (limit value setting to DIN 16086) **) with temperature fluctuations < 10 K ***) in % of the span per year
---------	--

Pack quantity [piece]	1
-----------------------	---