



Manometer Pressure Gauges

Manometer NG XX - XX - XX - X - X

Model Code

Manometer NG **63** - **25** **1/4** **B** - **Bottom**

Description

Intended for adverse service conditions where vibration and pulsation exist. The HYDAC range of manometers are also suitable for gaseous or liquid media that will not obstruct the pressure system or attack copper alloy parts.

Features

- Copper alloy wetted parts
- Stainless steel case
- Glycerine filled

Manometer Pressure Gauges

Type

- 63 = 63mm gauge
- 100 = 100mm gauge

Pressure rating scale (bar)

- 1/0 = -1 to 0 bar pressure gauge
- 1/3 = -1 to 3 bar pressure gauge
- 0/4 = 0 to 4 bar pressure gauge
- 0/6 = 0 to 6 bar pressure gauge
- 10 = 10 bar pressure gauge
- 16 = 16 bar pressure gauge
- 25 = 25 bar pressure gauge
- 40 = 40 bar pressure gauge
- 60 = 60 bar pressure gauge
- 100 = 100 bar pressure gauge
- 160 = 160 bar pressure gauge
- 250 = 250 bar pressure gauge
- 400 = 400 bar pressure gauge
- 600 = 600 bar pressure gauge

Process connection

- 1/4 = G1/4" BSPP
- 1/2 = G1/2" BSPP

Connection type

- B = BSPP connection
- NPT = NPT connection

Gauge Connection

- Bottom = Direct bottom connection
- Rear = Direct rear connection