




# SD2000

SDR21DGXFPKG/US-100



Flow sensors



1: 4-digit alphanumeric display

2: Programming buttons



## Product characteristics

Compressed air meter

Quick disconnect

Process connection: R2 (DN50)

Function programmable

2 outputs

OUT1: flow monitoring (binary), quantity meter (pulse), preset counter (binary)

OUT2: flow or temperature monitoring (analogue or binary)

flow monitoring

Display range

0...840 Nm<sup>3</sup>/h

Measuring range

2.3 (3)...700 Nm<sup>3</sup>/h \*

Temperature monitoring

Display range

-12...72 °C

## Application

Application

Compressed air  
Air quality(ISO 8573-1):  
Class 141 (measuring error: see below, value A)  
Class 344 (measuring error: see below, value B)

Pressure rating

[bar]

16

Medium temperature

[°C]

0...60

## Electrical data

Electrical design

DC PNP

Operating voltage

[V]

18...30 DC <sup>1)</sup>

Current consumption

[mA]

< 110

Protection class

III

Reverse polarity protection

yes

## Outputs

Output function

OUT1: normally open / closed programmable or pulse

OUT2: normally open / closed programmable or analog (4...20 mA scaleable)

Current rating

[mA]

2 x 250

Voltage drop

[V]

< 2

Short-circuit protection

yes (non-latching)



# SD2000

SDR21DGXFPKG/US-100



Flow sensors

Overload protection		yes
Analog output		4...20 mA
Max. load	[Ω]	< 500
Pulse output		consumed quantity meter

## Measuring / setting range

Flow monitoring			
Measuring range		2.3 (3)...700 *) Nm <sup>3</sup> /h	0.039 (0.04)...11.66 *) Nm <sup>3</sup> /min
Display range		0...840 Nm <sup>3</sup> /h	0.00...13.99 Nm <sup>3</sup> /min
Set point, SP		5...700 Nm <sup>3</sup> /h	0.09...11.66 Nm <sup>3</sup> /min
Reset point, rP		2...697 Nm <sup>3</sup> /h	0.04...11.61 Nm <sup>3</sup> /min
Analog start point, ASP		0...525 Nm <sup>3</sup> /h	0.00...8.75 Nm <sup>3</sup> /min
Analog end point, AEP		175...700 Nm <sup>3</sup> /h	2.91...11.66 Nm <sup>3</sup> /min
in steps of		1 Nm <sup>3</sup> /h	0.01 Nm <sup>3</sup> /min
Volumetric flow quantity monitoring			
Pulse value			0.010...4000000 m <sup>3</sup>
in steps of			0.010 m <sup>3</sup>
Pulse length	[s]		≥ 0.021 / ≤ 2
Temperature monitoring			
Measuring range	[°C]		0...60
Display range	[°C]		-12...72

## Accuracy / deviations

Flow monitoring			
Accuracy (within measuring range)		A): ± (3% MW + 0.3% MEW) / B): ± (6% MW + 0.6% MEW) ***)	
Repeatability[% of the measured value]		± 1.5	
Temperature monitoring			
Accuracy	[K]	± 2 **)	

## Reaction times

Power-on delay time	[s]	1
Flow monitoring		
Response time	[s]	< 0.1 (dAP = 0)
Damping, dAP	[s]	0 - 0.2 - 0.4 - 0.6 - 0.8 - 1

## Software / programming

Programming options		hysteresis / window function; N.O. / N.C; current / pulse output; display can be rotated / deactivated; display unit, totalizer
---------------------	--	---

## Interfaces

IO-Link Device		
Transfer type		COM2 (38.4 kBaud)
IO-Link revision		1.1
SDCI standard		IEC 61131-9 CDV
IO-Link Device ID		270 d / 00 01 0E h
Profiles		no profile
SIO mode		yes
Required master port class		A
Process data analogue		3
Process data binary		2



# SD2000

SDR21DGXFPKG/US-100



Flow sensors

Min. process cycle time	[ms]	4.1 ms
<b>Environment</b>		
Ambient temperature	[°C]	0...60
Storage temperature	[°C]	-20...85
Max. relative air humidity	[%]	90
Protection		IP 65
<b>Tests / approvals</b>		
Pressure equipment directive		article 3, section 3 - sound engineering practice
EMC		DIN EN 61000-6-2 DIN EN 61000-6-3
Vibration resistance		DIN EN 68000-2-6: 5 g (55...2000 Hz)
MTTF	[Years]	227
<b>Mechanical data</b>		
Process connection		R2 (DN50)
Materials (wetted parts)		stainless steel (304S15); FKM; ceramics: glass passivated; PEEK GF30; polyester; aluminum
Housing materials		PBT-GF 20; NBR; PC (polycarbonate); stainless steel (304S15); PTFE; brass coated; FKM; aluminum powder-coated
Weight	[kg]	4.35
<b>Displays / operating elements</b>		
Display		Display unit 5 x LED green (Nm³/min, Nm³/h, Nm/s, Nm³, °C) Function display 1 x LED green Switching status 2 x LED yellow Measured values 4-digit alphanumeric display Programming 4-digit alphanumeric display
<b>Electrical connection</b>		
Connection		M12 connector
<b>Wiring</b>		
OUT1/IO-Link: 3 selection options		
- switching output flow rate monitoring		
- pulse output quantity meter		
- signal output preset counter		
OUT2/InD: 5 selection options		
- switching output flow rate monitoring		
- switching output temperature monitoring		
- analogue output flow rate		
- analogue output temperature		
- input signal counter reset		
<b>Remarks</b>		
Remarks		<ul style="list-style-type: none"> <li>1) to EN50178, SELV, PELV</li> <li>*) in brackets: displayed value</li> <li>**) medium flow in the limit area of the flow measurement range</li> <li>***) under conditions acc. to DIN ISO 2533 and when installed in DN50 pipes</li> <li>MW = measured value</li> <li>MEW = final value of the measuring range</li> <li>Measuring, display and setting ranges refer to standard volume flow according to DIN ISO 2533.</li> <li>For information about installation and operation please see the operating instructions.</li> </ul>
Pack quantity	[piece]	1