



## Electronic Pressure Switch EDS 4100 ATEX Intrinsicly Safe



(Minimum order quantity 50 units)

### Description:

The pressure switch EDS 4100 in ATEX version, has been specially developed for use in potentially explosive atmospheres, and is based on the EDS 4000 series.

The switching point and switch-back point, the function of the switching outputs as N/C or N/O and the switching delay are factory-set according to customer requirement (not field-adjustable).

As with the industry model, the EDS 4100 in ATEX version has a ceramic measurement cell with thick-film strain gauge for measuring absolute pressure in the low pressure range.

With approval for the following

### Protection types and applications:

I M1 Ex ia I  
II 1G Ex ia IIC T4, T5, T6  
II 1/2G Ex ia IIC T4, T5, T6  
II 2G Ex ia IIC T4, T5, T6  
II 1 D Ex iaD 20 T100 °C

almost all requirements are covered regarding ignition group, error class and temperature class.

Versions for other Protection types and applications are available on request.

### Special features:

- Switching output factory-set (not field-adjustable)
- Accuracy  $\leq \pm 1\%$  FS
- Certificates:  
DEKRA EXAM BVS 07 ATEX E 041 X
- Various types of electrical connection
- Very small temperature error
- Excellent EMC characteristics
- Excellent durability

### Technical data:

| Input data                   |   |
|------------------------------|---|
| Measuring ranges             | 1; 2.5 bar  |
| Overload pressures           | 3; 8 bar  |
| Burst pressures              | 5; 12 bar   |
| Mechanical connection        | G1/4 A DIN 3852   |
| Torque value                 | 20 Nm   |
| Parts in contact with medium | Sensor: Ceramic<br>Mech. connection: 1.4301<br>Seal: FPM / EPDM |

| Output data  |   |
|--|---|
| Switch output                                      | 1 x PNP N/C or N/O  |
| Output load  | during operation: $I_{max} \leq 34$ mA  |
| Switching point                                    | factory-set to customer specification   |
| Switch-back point                                  | factory-set to customer specification   |
| Accuracy to DIN 16086,<br>Max. setting             | $\leq \pm 0.5\%$ FS typ.<br>$\leq \pm 1\%$ FS max.                                |
| Repeatability                                      | $\leq \pm 0.1\%$ FS at 25 °C  |
| Temperature drift                                  | $\leq \pm 0.03\%$ FS / °C max. zero point<br>$\leq \pm 0.03\%$ FS / °C max. range |
| Rising switch point and falling switch point delay | 32 ms standard<br>(8 .. 2000 ms factory-set to customer spec.)                    |
| Long-term drift                                    | $\leq \pm 0.3\%$ FS typ. / year   |

| Environmental conditions                                    |   |
|---|---|
| Storage temperature range                                   | -40 .. +100 °C  |
| Fluid temperature range                                     | -20 .. +60 °C / +70 °C / +85 °C   |
| CE mark   | EN 61000-6-1 / 2 / 3 / 4<br>EN 60079-0 / 11 / 26<br>EN 61241-0 / 11<br>EN 50303                 |
| Vibration resistance to<br>DIN EN 60068-2-6 at 10 .. 500 Hz | $\leq 20$ g   |
| Protection class to IEC 60529                               | IP 65 (male to EN175301-803 (DIN 43650))<br>IP 67 (M12x1 male, when an IP 67 connector is used) |

### Relevant data for Ex applications

|                                    | I M1<br>II 1G, 1/2G, 2G   | II 1 D            |
|------------------------------------|---|-------------------|
| Supply voltage                     | 14 .. 28 V DC   |                   |
| Compensated temperature range      | T6: -20 .. +60 °C<br>T5, T4: -20 .. +70 °C<br>T100: -25 .. +70 °C |                   |
| Operating temperature range        | T6: -20 .. +60 °C<br>T5, T4: -20 .. +70 °C<br>T100: -20 .. +70 °C |                   |
| Max. ambient temperature $T_a$     | T6: +60 °C<br>T5, T4: +70 °C                                      | T100: +70 °C      |
| Max. input current                 | 100 mA  | 93 mA             |
| Max. input power                   | 0.7 W   | 0.65 W            |
| Max. internal capacitance          | 33 nF   | 33 nF             |
| Max. internal inductance           | 0 mH  | 0 mH              |
| Insulation voltage <sup>1)</sup>   | 50 V AC, with integrated overvoltage protection EN 61000-6-2      |                   |
| Approved intrinsic safety barriers | Pepperl & Fuchs:<br>Telematic Ex STOCK:                           | Z 787<br>MTL 7087 |

| Other data                        |                                      |
|-----------------------------------|--------------------------------------|
| Residual ripple of supply voltage | $\leq 5\%$                           |
| Life expectancy                   | > 10 million cycles<br>0 .. 100 % FS |
| Weight                            | ~ 150 g                              |

Note: Reverse polarity protection of the supply voltage, excess voltage, override and short circuit protection are provided.


FS (Full Scale) = relative to the full measuring range

<sup>1)</sup> 500 V AC on request


## Pin connections:

Pin connections are configured according to customer specification.

EN175301-803 (DIN 43650)



M12x1



## Safety instructions:

- The switching output draws the switching energy from the power supply to the pressure switch. No additional energy is introduced into the electrical circuit through the switching output.
- Dual Zener barriers specified and approved in the technical data must be used to connect the pressure switch. These have a reverse polarity diode to decouple the signal. The signal path may only be passively loaded.
- Ensure that the measured fluids in contact with the pressure switch are compatible with the materials used.

## Note:

The information in this brochure relates to the operating conditions and applications described. For applications or operating conditions not described, please contact the relevant technical department. Subject to technical modifications.

**HYDAC ELECTRONIC GMBH**  
Hauptstraße 27, D-66128 Saarbrücken  
Telephone +49 (0)6897 509-01  
Fax +49 (0)6897 509-1726  
E-mail: [electronic@hydac.com](mailto:electronic@hydac.com)  
Internet: [www.hydac.com](http://www.hydac.com)

## Areas of application:

| Protection Type    | I M1 Ex ia I  | II 1G Ex ia IIC<br>T4, T5, T6  | II 2G Ex ia IIC<br>II 1/2G Ex ia IIC<br>T4, T5, T6  | II 1D Ex iaD 20<br>T100 °C   |
|--------------------|---|--|---|--|
| Certificate        | DEKRA EXAM<br>BVS 07 ATEX<br>E 041 X  | DEKRA EXAM<br>BVS 07 ATEX<br>E 041 X   | DEKRA EXAM<br>BVS 07 ATEX<br>E 041 X  | DEKRA EXAM<br>BVS 07 ATEX<br>E 041 X   |
| Zones / Categories | Group I<br>Category M1<br>Mining<br>Protection class:<br>intrinsically safe ia with barrier | Group II<br>Category 1G<br>Gases<br>Protection class:<br>intrinsically safe ia with barrier<br>For use in Zone 0 | Group II<br>Category 2G, 1/2G<br>Gases<br>Protection class:<br>intrinsically safe ia with barrier<br>For use in Zone 1, 2<br>For mounting to Zone 0 | Group II<br>Category iD<br>Dusts<br>Protection class:<br>intrinsically safe ia with barrier<br>For use in Zone 20, 21, 22<br>For mounting to Zone 20 |
|                    |   | T4, T5: $T_a = 70\text{ °C}$<br>T6: $T_a = 60\text{ °C}$   | T4, T5: $T_a = 70\text{ °C}$<br>T6: $T_a = 60\text{ °C}$  | T100: $T_a = 70\text{ °C}$   |

Instruments for other protection types and applications are available on request. Please contact our technical sales department for more information.

## Order details:

The electronic pressure switch EDS 4100 in ATEX version has been specially developed for OEM customers and is available for minimum order quantities of 50 pieces per type. For exact specification, please contact the Sales Department of HYDAC ELECTRONIC.

## Accessories:

Appropriate accessories, such as electrical connectors can be found in the Accessories brochure.

## Dimensions:

