

Remote Control System G4 Mini Linear 4 PWM AMP-JPT



A complete remote control system solution using the PCU Mini Economy with linear levers suited for a 4, 5 or 6 section directional control valve using a PWM solenoid with AMP-JPT connectors

Scope of delivery

Item no.	Description
1	G4 Portable Control Unit MINI Linear-4
1	G4 Central Unit
1	G4 Standard supply cable kit
1	Standard valve cable kit 1-6 A/B AMP-JPT
1	Standard battery charger
2	Standard battery pack
1	Standard carrying strap
1	Emergency stop box
1	Pairing plug
1	Instruction manual RC400 G4

Quick system description

- 12 or 24 V DC Supply voltage
- Portable Control Unit equipped with 4 linear levers for control of 4 (+2) bi-directional analogue functions
- Function shift button allowing additional 2 bi-directional analogue functions as well as 6 digital functions using the 4 push buttons.
- Radio communication at 434 or 900 MHz (ISM-band) using frequency jumping technology
- All analogue functions programmable for final adjustment of speeds
- Complete cable kits for simple installation of supply, digital functions, dump valve and analogue functions
- Standard accessories included such as batteries, battery charger, neck strap and emergency stop button. See below for full system consistency

Order information

Radio / Region	Supply voltage	PWM outputs	Order reference
EUROPE	24 V DC	250 – 640 mA (100 Hz)	69108
EUROPE	12 V DC	500 – 1200 mA (100 Hz)	44875OU1142
NAFTA	24 V DC	250 – 640 mA (100 Hz)	69107
NAFTA	12 V DC	500 – 1200 mA (100 Hz)	44875OU1144

Note

The information in this brochure relates to the operating conditions and applications described.

For applications or operating conditions not described, please contact the relevant technical department. Subject to technical modifications.



Nordhydraulic
HYDAC INTERNATIONAL

Head Office
HYDAC INTERNATIONAL
GMBH

Industriegebiet
66380 Sulzbach/Saar
Germany

Phone: +49 6897 509-01
Fax: +49 6897 509-577

E-mail: mobilevalves@hydac.com
Internet: www.hydac.com