HYDRAULIC POWER UNIT ORDER FORM



CLIENT															
Contact person (Name, phone, email)	ail)														
Data about power pack															
Tank volume, I				Voltage of electric engine								Power of electric engine, kW			
Working pressure, MPa		ngle-phase 0V, 50 Hz	Three-phase 220/380V, 50 Hz				Other								
Type of pump		Ī		Flow, I/min			Numbe exit po				orts				
Number of pumps											(worki				
Working items (motors, cylinders, etc.)			Pressure (e	Speed (time of cycle)			Characteristics: – for motor: volume – for cylinder: Øpiston, Ørod, rod stroke								
1.															
2.															
3.															
4.															
5.															
Working fluid (oil, etc.)				air water without									na	\Box	
Cooling of the working fluid							T								
Heating of the working fluid with heating without heating Type of control															
electric V			Ιп									ınual			
pneumatic			mixed												
	Operating mode														
Control panel			autoi					-automatic			manual				
Filtration system															
Filter in s			iction line				return			n line					
Filtration, micron		60	90	250	3	6	10	16	25	3	6	10	16	25	
Special requirement											•				
Purpose of the unit															
What else is needed (cylinder, pressure hoses, tubes, motors, etc.):															
Comments															

DESIGN OF THE DRIVE





1. Vertical axis with submersed pump



3. Under the reservoir



5. Beneath the reservoir on separate frame



2. Horizontal axis with external pump



4. Beneath the reservoir on the frame



6. Beneath the reservoir in the pallet